

	REV	Description:	Tag No.	P-05	4	18-Jan-12	Frank				
					5	20-Feb-12	Frank				
					A00	7-Apr-17	Frank				
1		NUMBER REQUIRED:	2	SPEC NO.:							
2		MANUFACTURER:	Dalian Deep Blue Pump Co.,Ltd		PURCHASE ORDER NO.:						
3		SIZE & TYPE:	DCSG 400-120X4		BB5	SERIAL NO.:					
4		APPLICABLE TO:	<input type="radio"/> PROPOSALS <input type="radio"/> PURCHASE <input checked="" type="checkbox"/> AS BUILT								
5		NOTES:	INFORMATION BELOW TO BE COMPLETED: <input type="radio"/> BY PURCHASER <input type="checkbox"/> BY MANUFACTURER <input checked="" type="checkbox"/> BY MANUFACTURER OR PURCHASER								
6		<input checked="" type="radio"/> OPERATING CONDITIONS (5.1.3)				<input checked="" type="radio"/> LIQUID (5.1.3)					
7		CAPACITY, NORMAL	309	(m³/h)	RATED	402	(m³/h)	LIQUID TYPE OR NAME			
8		OTHER					STABILISED HEAVY CRUDE OIL				
9		SUCTION PRESSURE RATED/MAX.	4.89	/	18	(barg)	<input checked="" type="radio"/> HAZARDOUS <input checked="" type="radio"/> FLAMMABLE <input type="radio"/> (5.1.5)				
10		DISCHARGE PRESSURE	31.6	(barg)					MIN.	NORMAL	MAX.
11		DIFFERENTIAL PRESSURE	26.7	(bar)					6		60
12		DIFF. HEAD	307.0	(m)	NPSHA	57.4	(m)	PUMPING TEMP (°C)	0.22	0.93	
13		PROCESS VARIATIONS (5.1.4)					VAPOR PRESS. (bar)	0.928	0.887		
14		STARTING CONDITIONS (5.1.4)					RELATIVE DENSITY (SG):	51.7	11.4		
15		SERVICE:	<input checked="" type="radio"/> CONT. <input type="radio"/> INTERMITTENT (STARTS/DAY)				VISCOSITY (cP)	1.67~1.9 (kJ/kg °C)			
16		<input type="radio"/> PARALLEL OPERATION REQ'D (5.1.13)					SPECIFIC HEAT, Cp	10 PTB BS &W (PPM)			
17		<input checked="" type="radio"/> SITE DATA (5.1.3)					<input checked="" type="radio"/> CHLORIDE CONCENTRATION	15PPM by Wt (PPM) WET (5.2.1.12c)			
18		LOCATION: (5.1.30)					<input checked="" type="radio"/> H <sub>2</sub> S CONCENTRATION (6.5.2.4)	H <sub>2</sub> S, CO <sub>2</sub> , Cl' (5.12.1.9)			
19		<input type="radio"/> INDOOR <input type="radio"/> HEATED <input checked="" type="radio"/> OUTDOOR <input checked="" type="radio"/> UNHEATED					CORROSIVE / EROSION AGENT	H <sub>2</sub> S, CO <sub>2</sub> , Cl' (5.12.1.9)			
20		<input checked="" type="radio"/> ELECTRICAL AREA CLASSIFICATION (5.1.24 / 6.1.4)					MATERIALS				
21		TEMP. CL	T3	GR	IIB	Zone	2	<input checked="" type="radio"/> ANNEX H CLASS (5.12.1.1) S-6			
22		<input type="radio"/> WINTERIZATION REQ'D <input checked="" type="radio"/> TROPICALIZATION REQ'D.					<input type="radio"/> MIN DESIGN METAL TEMP (5.12.4.1) (°C)				
23		SITE DATA (5.1.30)	Refer spec: YAP1-CTEP00-SAEM-SPJB-1001				<input type="radio"/> REDUCED HARDNESS MATERIALS REQ'D. (5.12.1.11)				
24		<input checked="" type="radio"/> ALTITUDE	10	(m)	BAROMETER	(bar)	<input checked="" type="checkbox"/> BARREL/CASE C.S IMPELLER 12%CHr				
25		<input checked="" type="radio"/> RANGE OF AMBIENT TEMPS: MIN/MAX.	-4	/	52	(°C)	<input checked="" type="checkbox"/> CASE/IMPELLER WEAR RINGS 12%CHr				
26		<input checked="" type="radio"/> RELATIVE HUMIDITY: MIN / MAX	/	100	(%)	<input checked="" type="checkbox"/> SHAFT AISI4140					
27		UNUSUAL CONDITIONS: (5.1.30)	<input checked="" type="radio"/> DUST <input type="radio"/> FUMES				<input checked="" type="checkbox"/> DIFFUSERS 12%CHr				
28		<input checked="" type="radio"/> OTHER	Temporary Sand Storm				<input checked="" type="checkbox"/> PERFORMANCE:				
29							PROPOSAL CURVE NO.				
30							<input checked="" type="checkbox"/> RPM 2980				
31		<input checked="" type="radio"/> DRIVER TYPE					<input checked="" type="checkbox"/> IMPELLER DIA. RATED 285 MAX. 330 MIN. 275 (mm)				
32		<input checked="" type="radio"/> INDUCTION MOTOR <input type="radio"/> STEAM TURBINE <input type="radio"/> GEAR					<input checked="" type="checkbox"/> IMPELLER TYPE Closed Type				
33		<input type="radio"/> OTHER					<input checked="" type="checkbox"/> RATED POWER 452 (kW) EFFICIENCY 68 (%)				
34							<input checked="" type="checkbox"/> MINIMUM CONTINUOUS FLOW:				
35		<input checked="" type="radio"/> MOTOR DRIVER (6.1.1 / 6.1.4)					THERMAL (m³/h) STABLE 61.8 (m³/h)				
36		<input checked="" type="radio"/> MANUFACTURER	ABB				<input checked="" type="checkbox"/> PREFERRED OPER. REGION 280 TO 440 (m³/h)				
37		<input checked="" type="checkbox"/> 630 (kW) <input checked="" type="checkbox"/> 2980 (RPM)					<input checked="" type="checkbox"/> ALLOWABLE OPER. REGION 61.8 TO 480 (m³/h)				
38		<input checked="" type="checkbox"/> FRAME AMD500L2T <input checked="" type="checkbox"/> ENCLOSURE IP55W					<input checked="" type="checkbox"/> MAX HEAD @ RATED IMPELLER 506 (m)				
39		<input checked="" type="radio"/> HORIZONTAL <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> SERVICE FACTOR					<input checked="" type="checkbox"/> MAX POWER @ RATED IMPELLER 540 (kW)				
40		<input checked="" type="radio"/> VOLTS/PHASE/HERTZ	6000V	/	3	/	50	<input checked="" type="checkbox"/> NPSHR AT RATED CAPACITY 10 (m) (5.1.10)			
41		<input type="radio"/> TYPE	Induction Type				<input checked="" type="checkbox"/> SUCTION SPECIFIC SPEED 9121 (US)				
42		<input type="radio"/> MINIMUM STARTING VOLTAGE (6.1.5)					MAX/ACTUAL / (5.1.11)				
43		<input checked="" type="radio"/> INSULATION F <input checked="" type="radio"/> TEMP. RISE B					<input checked="" type="checkbox"/> MAX. SOUND PRESS. LEVEL REQ'D 85 @ 1m(Note 1) (dBA) (5.1.16)				
44		<input checked="" type="checkbox"/> FULL LOAD AMPS	70A				<input type="checkbox"/> EST MAX SOUND PRESS. LEVEL (dBA) (5.1.16)				
45		<input checked="" type="checkbox"/> LOCKED ROTOR AMPS	371A				<input type="radio"/> UTILITY CONDITIONS				
46		<input checked="" type="radio"/> STARTING METHOD	DOL				ELECTRICITY				
47		<input checked="" type="radio"/> LUBE	OIL				VOLTAGE				
48		BEARINGS (TYPE/NUMBER):					PHASE				
49		<input checked="" type="checkbox"/> RADIAL	6317M/C3	/	1	HERTZ					
50		<input checked="" type="checkbox"/> THRUST	6317M/C3	/	1	DRIVERS					
51		<input type="checkbox"/> VERTICAL THRUST CAPACITY					HEATING				
52		UP (N) DOWN (N)					SYSTEM VOLTAGE DIP <input type="radio"/> 80% <input checked="" type="radio"/> OTH YAP1-AAAA81-MEEL-SPEQ-1005				
53							STEAM				
54							MAX. PRESS.				
55							MAX. TEMP.				
56							MIN. PRESS.				
57							MIN. TEMP.				
58							COOLING WATER: (5.1.19) SOURCE				
59							SUPPLY TEMP. N.A (°C) MAX. RETURN TEMP. (°C)				
60							NORM. PRESS. N.A (bar) DESIGN PRESS. (bar)				
61							MIN. RET. PRESS. N.A (bar) MAX. ALLOW. D.P. (bar)				
62							CHLORIDE CONCENTRATION: (PPM)				

Description	Rev.	Tag No.	P-0	4	18-Jan-12	Frank		
				5	20-Feb-12	Frank		
				A00	7-Apr-17	Frank		
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								
58								
59								
60								

**NOTES:**      1 Motor datasheet will be submiited separately.  
2 This pump can be self-vent.So there is no vent.  
3 There is no extra pressured lub oil system,since the ring oil is appliable.  
4 The procured mechanical seal plan 11+53B is suitable for this case.

	REV	Description:	Tag No.	P-05	4	18-Jan-12	Frank		
					5	20-Feb-12	Frank		
					A00	7-Apr-17	Frank		

  

1	<b>CONSTRUCTION</b>				<b>SURFACE PREPARATION AND PAINT</b>																									
2	<b>ROTATION:</b> (VIEWED FROM COUPLING END) <input checked="" type="checkbox"/> CW <input type="checkbox"/> CCW				<input type="checkbox"/> MANUFACTURER'S STANDARD <input checked="" type="checkbox"/> OTHER (SEE BELOW)																									
3	<b>PUMP TYPE:</b> (1.3)				<b>YAPI-CTEP00-SAMW-SPPA-1001</b>																									
4	<input type="checkbox"/> BB1 <input type="checkbox"/> BB2 <input type="checkbox"/> BB3 <input checked="" type="checkbox"/> BB5				<b>SPECIFICATION NO.</b>																									
5	<b>CASING MOUNTING:</b>				<b>PUMP:</b>																									
6	<input checked="" type="checkbox"/> CENTERLINE <input type="checkbox"/> NEAR CENTERLINE				<input type="checkbox"/> PUMP SURFACE PREPARATION																									
7	<input type="checkbox"/> FOOT				<input type="checkbox"/> PRIMER																									
8	<b>CASING SPLIT:</b>				<input type="checkbox"/> FINISH COAT																									
9	<input type="checkbox"/> AXIAL <input checked="" type="checkbox"/> RADIAL				<b>BASEPLATE: (6.3.17)</b>																									
10	<b>CASING TYPE:</b>				<input type="checkbox"/> BASEPLATE SURFACE PREPARATION																									
11	<input type="checkbox"/> SINGLE VOLUTE <input type="checkbox"/> MULTIPLE VOLUTE <input checked="" type="checkbox"/> DIFFUSER				<input type="checkbox"/> PRIMER																									
12	<input checked="" type="checkbox"/> BETWEEN BEARINGS <input checked="" type="checkbox"/> BARREL				<input type="checkbox"/> FINISH COAT																									
13	<b>CASE PRESSURE RATING:</b>				<input checked="" type="checkbox"/> DETAILS OF LIFTING DEVICES(6.3.20)																									
14	<input checked="" type="checkbox"/> MAX ALLOWABLE WORKING PRESSURE <b>69</b> (bar)				<b>SHIPMENT: (7.4.1)</b>																									
15	@ <b>6/175</b> (°C)				<input type="checkbox"/> DOMESTIC <input checked="" type="checkbox"/> EXPORT <input checked="" type="checkbox"/> EXPORT BOXING REQUIRED																									
16	<input checked="" type="checkbox"/> HYDROTEST PRESSURE <b>104</b> (bar)				<input checked="" type="checkbox"/> OUTDOOR STORAGE MORE THAN 12 MONTHS																									
17	<input type="checkbox"/> SUCTION PRESS. REGIONS MUST BE DESIGNED				<b>SPARE ROTOR ASSEMBLY PACKAGED FOR:</b>																									
18	FOR MAWP (5.3.6)				<input type="checkbox"/> SHIPPING CONTAINER (8.2.8.3) <input type="checkbox"/> VERTICAL STORAGE (8.2.8.2)																									
19	<input checked="" type="checkbox"/> <b>NOZZLE CONNECTIONS: (5.4.2)</b>				<input type="checkbox"/> TYPE OF SHIPPING PREPARATION <input type="checkbox"/> N2 PURGE (8.2.8.4)																									
20	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:15%;">SIZE</td> <td style="width:15%;">FLANGE RATING</td> <td style="width:15%;">FACING</td> <td style="width:15%;">POSITION</td> </tr> <tr> <td>250</td> <td>600lb</td> <td>RF</td> <td>TOP</td> </tr> <tr> <td>200</td> <td>600lb</td> <td>RF</td> <td>TOP</td> </tr> </table>				SIZE	FLANGE RATING	FACING	POSITION	250	600lb	RF	TOP	200	600lb	RF	TOP	<b>HEATING AND COOLING</b>													
SIZE	FLANGE RATING	FACING	POSITION																											
250	600lb	RF	TOP																											
200	600lb	RF	TOP																											
21	SUCTION				<input type="checkbox"/> HEATING JACKET REQ'D. (5.8.9) <input type="checkbox"/> COOLING REQ'D.																									
22	DISCHARGE				<input checked="" type="checkbox"/> COOLING WATER PIPING PLAN (6.5.4.1)																									
23	BALANCE DRUM				C.W. PIPING:																									
24	PRESSURE CASING AUX. CONNECTIONS: (5.4.3)				<input checked="" type="checkbox"/> PIPE <input type="checkbox"/> TUBING;    FITTINGS																									
25	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:15%;">NO.</td> <td style="width:15%;">SIZE (NPS)</td> <td style="width:15%;">TYPE</td> </tr> <tr> <td>1</td> <td>20</td> <td>FLANGE</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table>				NO.	SIZE (NPS)	TYPE	1	20	FLANGE																C.W. PIPING MATERIALS:				
NO.	SIZE (NPS)	TYPE																												
1	20	FLANGE																												
26	DRAIN				<input type="checkbox"/> S. STEEL <input type="checkbox"/> C. STEEL <input type="checkbox"/> GALVANIZED																									
27	COOLING				COOLING WATER REQUIREMENTS:																									
28	PRESS. GAUGE				<input type="checkbox"/> BEARING HOUSING (m³/h) @ (bar)																									
29	TEMP GAUGE				<input type="checkbox"/> HEAT EXCHANGER (m³/h) @ (bar)																									
30	WARM-UP				STEAM PIPING: <input type="checkbox"/> TUBING <input type="checkbox"/> PIPE																									
31	BALANCE / LEAK-OFF				<b>BEARINGS AND LUBRICATION</b>																									
32	MACHINED AND STUDDED CONNECTIONS (5.4.3.8)				BEARING (TYPE/NUMBER) (5.10.1):																									
33	CYLINDRICAL THREADS REQUIRED (5.4.3.3)				<input checked="" type="checkbox"/> RADIAL <b>Sliding Bearing</b> / <b>Z90(Sleeve type)</b>																									
34	<b>ROTOR:</b>				<input checked="" type="checkbox"/> THRUST <b>Antifriction bearing</b> / <b>7315BECBM</b>																									
35	COMPONENT BALANCE TO ISO 1940 G1.0 (5.9.4.4)				LUBRICATION (5.11.3, 5.11.4):																									
36	SHRINK FIT -LIMITED MOVEMENT IMPELLERS (8.2.2.3)				<input checked="" type="checkbox"/> RING OIL <input type="checkbox"/> HYDRODYNAMIC <input type="checkbox"/> PURGE OIL MIST <input type="checkbox"/> PURE OIL MIST																									
37	<b>COUPLINGS:(6.2.2)</b> (Remark 1)				<input type="checkbox"/> CONSTANT LEVEL OILER PREFERENCE (5.10.2.2):																									
38	<input checked="" type="checkbox"/> MANUFACTURER <b>Metastream</b> <input checked="" type="checkbox"/> MODEL <b>Flexible with spacer</b>				<input type="checkbox"/> PRESSURE LUBE SYS.ISO13709-3 <input type="checkbox"/> ISO 13709-2 (8.2.6.1/8.2.6.5)																									
39	<input type="checkbox"/> RATING (KW/100 RPM)				<input checked="" type="checkbox"/> OIL VISC. ISO GRADE <b>VG46</b>																									
40	<input checked="" type="checkbox"/> SPACER LENGTH <b>250</b> (mm) <input checked="" type="checkbox"/> SERVICE FACTOR <b>1.5</b>				<input type="checkbox"/> OIL PRESS. TO BE GREATER THAN COOLANT PRESSURE																									
41	DRIVER HALF COUPLING MOUNTED BY:				<input type="checkbox"/> REVIEW AND APPROVE THRUST BEARING SIZE(8.2.5.2.4)																									
42																														

					4	18-Jan-12	Frank		
REV	Description:	Tag No.	P-05	5		20-Feb-12	Frank		
					A00	7-Apr-17	Frank		
1	SPARE PARTS (TABLE 18)				QA INSPECTION AND TESTING (CONT.)				
2	● START-UP	● NORMAL MAINTENANCE			TEST (7.3.1.2)	NON-WIT	WIT	OBSERVE	
3	● SPECIFY	2 YEARS OPERATING SPARE PARTS			● HYDROSTATIC (7.3.2)	○	●	○	
4					● PERFORMANCE (7.3.3)	○	●	○	
5	OTHER PURCHASER REQUIREMENTS				● NPSH (7.3.4.2)	○	●	○	
6	● COORDINATION MEETING REQUIRED (9.1.3)				● RETEST ON SEAL LEAKAGE (7.3.3.2d)	○	●	○	
7	● MAXIMUM DISCHARGE PRESSURE TO INCLUDE (5.3.2)				● RETEST REQUIRED AFTER FINAL	○	●	○	
8	● MAX RELATIVE DENSITY				HEAD ADJUSTMENT (7.3.3.5b)				
9	● MAX DIA. IMPELLERS AND/OR NO OF STAGES				● COMPLETE UNIT TEST (7.3.4.3)	○	●	○	
10	○ OPERATION TO TRIP SPEED				● SOUND LEVEL TEST (7.3.4.4)	○	●	○	
11	○ CONNECTION DESIGN APPROVAL (5.12.3.4/8.2.1.4)				● CLEANLINESS PRIOR TO	○	●	○	
12	○ INERT GAS INHIBITED STORAGE OF SPARE CARTRIDGE (8.2.8.3)				FINAL ASSEMBLY (7.2.2.2)				
13	○ TORSIONAL ANALYSIS REQUIRED (5.9.2.1)				○ NOZZLE LOAD TEST (6.3.6)	○	○	○	
14	○ TORSIONAL ANALYSIS REPORT (5.9.2.6)				○ CHECK FOR CO-PLANAR	○	○	○	
15	● PROGRESS REPORTS (9.3.3)				MOUNTING PAD SURFACES (6.3.3)				
16	● OUTLINE OF PROCEDURES FOR OPTIONAL TESTS (9.3.5)				○ MECHANICAL RUN UNTIL OIL	○	○	○	
17	○ ADDITIONAL DATA REQUIRING 20 YEARS RETENTION (7.2.2.1f)				TEMP. STABLE				
18	● LATERAL ANALYSIS REQUIRED (8.2.4.1 / 8.2.4.1.3)				● 4 HR. MECHANICAL RUN AFTER	○	●	○	
19	● DYNAMIC BALANCE ROTOR (8.2.4.2)				OIL TEMP. STABLE				
20	MANIFOLD PIPING TO SINGLE CONNECTION (6.5.1.6)				○ 4 HR. MECH. RUN TEST(7.3.4.7.2)	○	○	○	
21	● VENT ● DRAIN ○ COOLING WATER				○ TRUE PEAK VELOCITY	○	○	○	
22	○ MOUNT SEAL RESERVOIR OFF BASEPLATE (6.5.1.4)				DATA (7.3.3.4e)				
23	● FLANGES REQUIRED IN PLACE OF SOCKET WELD UNIONS (6.5.2.8)				○ BRG HSG RESONANCE	○	○	○	
24	CONNECTION BOLTING				TEST (7.3.4.6)				
25	○ PTFE COATING ○ ASTM A153 GALVANIZED				● REMOVE / INSPECT	○	●	○	
26	○ PAINTED ● SS				HYDRODYNAMIC BEARINGS				
27	● INSTALLATION LIST IN PROPOSAL (9.2.3L)				AFTER TEST (8.2.7.5)				
28	QA INSPECTION AND TESTING				○ AUXILIARY EQUIPMENT	○	○	○	
29	● SHOP INSPECTION (7.1.4)				TEST (7.3.4.5) (Note 1)				
30	● PERFORMANCE CURVE APPR.				○ CHARPY TEST (EN 13445/ASME VIII)	○	○	○	
31	○ TEST WITH SUBSTITUTE SEAL (7.3.3.2)				○ OIL SYSTEM CLEANLINESS (Note 1)	○	○	○	
32	● MATERIAL CERTIFICATION REQUIRED (5.12.1.8)				○	○	○	○	
33	● CASING ● IMPELLER ● SHAFT				○	○	○	○	
34	● OTHER	PER APPROVED QUALITY PLAN			● VENDOR KEEP REPAIR AND HT RECORDS (7.2.1.1c)				
35	○ CASTING REPAIR PROCEDURE APPROVAL REQ'D (5.12.2.5)				● VENDOR SUBMIT TEST PROCEDURES (7.3.1.2 / 9.2.5)				
36	● INSPECTION REQUIRED FOR CONNECTION WELDS (5.12.1.5)				● VENDOR SUBMIT TEST DATA WITHIN 24 HOURS (7.3.3.3c)				
37	○ MAG PARTICLE ● LIQUID PENETRANT				● INCLUDE PLOTTED VIBRATION SPECTRA (5.9.3.3)				
38	● RADIOGRAPHIC ○ ULTRASONIC				● RECORD FINAL ASSEMBLY RUNNING CLEARANCES				
39	● INSPECTION REQUIRED FOR CASTINGS (7.2.1.3)(5.12.1.5)				● COMPLETION OF INSPECTION CHECK LIST (7.1.6)				
40	○ MAG PARTICLE ● LIQUID PENETRANT								
41	● RADIOGRAPHIC ○ ULTRASONIC								
42	○ HARDNESS TEST REQUIRED: (7.2.2.3)								
43	○ ADDITIONAL SUBSURFACE EXAMINATION (7.2.1.1)								
44	FOR Shaft								
45	METHOD Ultrasonic								
46	REMARKS								
47	Note 1: There is no oil system and control system for these pumps.								
48									
49									
50									
51									
52									
53									
54									
55									
56									
57									
58									
59									
60									
61									

MR / PO No.			10GZ718	Service:		HEAVY CRUDE EXPORT PUMPS				3	31-Dec-11	Frank		
Description:	Revision:	Tag No.	P-05			4	18-Jan-12	Frank						
						5	20-Feb-12	Frank						
						A00	7-Apr-17	Frank						
1	PRESSURE VESSEL DESIGN CODE REFERENCES.													
2	<input type="checkbox"/> THESE REFERENCES MUST BE LISTED BY THE MANUFACTURER													
3	PRESSURE VESSEL DESIGN STANDARD USED TO DESIGN PRESSURE CASING(5.3.4) <input type="checkbox"/>													
4	CASTING FACTORS USED IN DESIGN( 5.3.2)(TABLE 2) <input type="checkbox"/>													
5	SOURCE OF MATERIAL PROPERTIES <input type="checkbox"/>													
6														
7	WELDING AND REPAIRS (5.12.3.1)													
8	THESE REFERENCES MUST BE LISTED BY THE PURCHASER. (DEFAULT TO TABLE 9 IF NO PURCHASER PREFERENCE IS STATED)													
9	<input type="radio"/> ALTERNATE WELDING CODES AND STANDARDS (5.12.3.1)													
10	Welding Requirement (Applicable Code or Standard)										Purchaser defined		Default per Table 10	
11	Welder/operator qualification										<input type="radio"/>		<input checked="" type="radio"/>	
12	Welding procedure qualification										<input type="radio"/>		<input checked="" type="radio"/>	
13	Non-pressure retaining structural welding such as baseplates or supports										<input type="radio"/>		<input checked="" type="radio"/>	
14	Magnetic particle or liquid penetrant examination of the plate edges										<input type="radio"/>		<input checked="" type="radio"/>	
15	Postweld heat treatment										<input type="radio"/>		<input checked="" type="radio"/>	
16	Postweld heat treatment of casing fabrication welds										<input type="radio"/>		<input checked="" type="radio"/>	
17														
18	MATERIAL INSPECTION (7.2.2.1)(7.2.1.3)													
19	THESE REFERENCES MUST BE LISTED BY THE PURCHASER (DEFAULT TO TABLE 13 IF NO PURCHASER PREFERENCE IS STATED)													
20	<input type="radio"/> ALTERNATIVE MATERIAL INSPECTIONS AND ACCEPTANCE CRITERIA (SEE TABLE 13)													
21	Type of inspection				Methods				For fabrications		Castings			
22	Radiography				<input type="radio"/>				<input type="radio"/>		<input type="radio"/>			
23	Ultrasonic inspection				<input type="radio"/>				<input type="radio"/>		<input type="radio"/>			
24	Magnetic particle inspection				<input type="radio"/>				<input type="radio"/>		<input type="radio"/>			
25	Liquid penetrant inspection				<input type="radio"/>				<input type="radio"/>		<input type="radio"/>			
26	REMARKS													
27														
28														
29														
30														
31														
32														
33														
34														
35														
36														
37														
38														
39														
40														
41														
42														
43														
44														
45														
46														
47														
48														
49														
50														
51														
52														
53														
54														
55														
56														
57														
58														
59														
60														
61														
62														