

DRILLING ACCESSORIES

Sr	Description/Specifications	Qty (Nos)
1.	HQWL double tube core swivel core barrel assembly 4 meter long heat treated hardening on both ends on outer tube / chrome plated ends.	04
2.	NQWL double tube core swivel core barrel assembly 4 meter long heat treated hardening on both ends on outer tube / chrome plated ends.	04
3.	NQWL impregnated diamond, "VV6" profile with 6 fluid ports core bit for medium hard to hard sandstone with limited silt and shale	25
4.	NQWL knuckle head assembly	06
5.	NQWL overshot assembly with releaser	06
6.	Over size NW impregnated diamond casing shoe with outer dia 97mm	06
7.	Over size HW impregnated casing shoe with outer dia 122mm	06
8.	Over size PW impregnated casing shoe with outer dia 150mm	06
9.	Impregnated diamond casing shoe suitable for 6" dia tricone roller rock bit with Box Size: PW casing, Length: 24 inches, Inner Dia: 6-1/4 inches, Outer Dia = 7 inches	02
10.	Impregnated diamond casing shoe suitable for 8" dia tricone roller rock bit with Box Size: PW casing, Length: 24 inches, Inner Dia: 8-1/4 inches, Outer Dia = 9 inches	02
11.	Impregnated diamond casing shoe suitable for 10" dia tricone roller rock bit with Box Size: PW casing, Length: 24 inches, Inner Dia: 10-1/4 inches, Outer Dia = 11 inches	02

Important Note:

1. Technical specifications of all accessories must be supported by literature/drawing etc.
2. No quotation without technical literature and drawings will be accepted.
3. Make and country of origin should be clearly mentioned in quotation.