

1. Butyl Rubber Sheet(Flexible) Thickness: 3mm

Qty:05 Sq.Mtr

Material	=Butyl
Color	= black
Thickness	= 3 mm
Shore Hardness	=65
Tensile Strength	=5 Mpa.
Minimum Temperature	= -35 °C
Maximum Temperature	=140 °C

2. Butyl Rubber Sheet(Flexible) Thickness: 01mm

Qty:05 Sq.Mtr

Material	=Butyl
Color	= black
Thickness	= 01 mm
Shore Hardness	=65
Tensile Strength	=5 Mpa.
Minimum Temperature	= -35 °C
Maximum Temperature	=140 °C

3. Dual Heat Shrinkable (PTFE+PFA) Tubing with thin walls

Qty:20Mtr

Subject Object Dia	=8 – 12 mm
Sheet Expansion ID:	=12 – 13 mm
After Shrinkable ID:	=08 mm

4. Dual Heat Shrinkable (PTFE+PFA) Tubing with thin walls

Qty:20Mtr

Subject Object Dia	=13 – 17 mm
Sheet Expansion ID:	=17.5 – 18 mm
After Shrinkable ID:	=13 mm

3/3

Qty:20Mtr

5. PTFE Heat Shrinkable Tubing

Subject Object Dia = 1 – 2.10 mm

Sheet Minimum Expansion ID: = 2.38 mm

After Maximum shrinkage ID: = 1.08 mm

6. PTFE Heat Shrinkable Tubing

Qty:20Mtr

Subject Object Dia = 2.2 – 7.10 mm

Sheet Minimum Expansion ID: = 7.92 mm

After Maximum shrinkage ID: = 2.31 mm

7. PTFE Heat Shrinkable Tubing

Qty:20Mtr

Subject Object Dia = 06 – 18.7 mm

Sheet Minimum Expansion ID: = 19.05 mm

After Maximum shrinkage ID: = 6.08 mm