1 Rotary Vacuum Pumps Specifications: Model: 2X-70A Type: Rotary Vane Mechanical Pump Pumping speed: 70 lit./sec. Ultimate vacuum: 6 x 10-2 mbar Pump speed: 420 rpm Electric motor: 3 phase, 50 Hz Dia of inlet port: 80 mm Complete unit with spares & all accessories. Make: Shanghi Vacuum Pump Works, China. 2 Spare Parts for Rotary Vane Mechanical Pump: (Model: 2X-70 A, Make: China) i. Check valve plate for gas blast valve (set) a) High grade discharge valve disc. Size: 59 x 256 x 2 mm b) Low grade discharge valve disc. Size: 59 x 45 x 2 mm ii. Rotary Vane Spring Size: Dia = 8 mm, L = 100 mm, Wire thickness = 01 mm iii. Pin for spring a) Size: 5 x 70 mm b) Size: 5 x 55 mm iv. Primary Vane v. Secondary Vane Vi. Secondary Vane Vi. Seals & O-Ring Kit (complete set) 04 No. 12 Nos.			
 Type: Rotary Vane Mechanical Pump Pumping speed: 70 lit./sec. Ultimate vacuum: 6 x 10-2 mbar Pump speed: 420 rpm Electric motor: 3 phase, 50 Hz Dia of inlet port: 80 mm Complete unit with spares & all accessories. Make: Shanghi Vacuum Pump Works, China. 2 Spare Parts for Rotary Vane Mechanical Pump: (Model: 2X-70 A, Make: China) Check valve plate for gas blast valve (set) High grade discharge valve disc. Size: 59 x 256 x 2 mm Low grade discharge valve disc. Size: 59 x 45 x 2 mm Rotary Vane Spring Rotary Vane Spring Size: Dia = 8 mm, L = 100 mm, Wire thickness = 01 mm Pin for spring Size: 5 x 70 mm Size: 5 x 55 mm Primary Vane Primary Vane Secondary Vane 	1		04 No.
i. Check valve plate for gas blast valve (set) a) High grade discharge valve disc. Size: 59 x 256 x 2 mm b) Low grade discharge valve disc. Size: 59 x 45 x 2 mm ii. Rotary Vane Spring Size: Dia = 8 mm, L = 100 mm, Wire thickness = 01 mm iii. Pin for spring a) Size: 5 x 70 mm b) Size: 5 x 55 mm 50 Nos. 25 Nos. 12 Nos. iv. Primary Vane V. Secondary Vane 12 Nos.		 Type: Rotary Vane Mechanical Pump Pumping speed: 70 lit./sec. Ultimate vacuum: 6 x 10⁻² mbar Pump speed: 420 rpm Electric motor: 3 phase, 50 Hz Dia of inlet port: 80 mm Complete unit with spares & all accessories. 	
a) High grade discharge valve disc. Size: 59 x 256 x 2 mm b) Low grade discharge valve disc. Size: 59 x 45 x 2 mm ii. Rotary Vane Spring Size: Dia = 8 mm, L = 100 mm, Wire thickness = 01 mm iii. Pin for spring a) Size: 5 x 70 mm b) Size: 5 x 70 mm c) Size: 5 x 55 mm iv. Primary Vane v. Secondary Vane 12 Nos.	2	Spare Parts for Rotary Vane Mechanical Pump: (Model: 2X-70 A, Make: China)	*
	i.	 a) High grade discharge valve disc. Size: 59 x 256 x 2 mm b) Low grade discharge valve disc. 	12 set
a) Size: 5 x 70 mm b) Size: 5 x 55 mm 50 Nos. 25 Nos. 12 Nos. v. Secondary Vane 12 Nos. 12 Nos.	ii.	Size: Dia = 8 mm, L = 100 mm,	50 Nos.
v. Secondary Vane 12 Nos.	iii.	a) Size: 5 x 70 mm	0000.
V. Secondary varie	iv.	Primary Vane	12 Nos.
vi. Seals & O-Ring Kit (complete set) 08 sets	٧.	Secondary Vane	12 Nos.
	vi.	Seals & O-Ring Kit (complete set)	08 sets