

HSCO DRILLS

A	HSCO Twist Drill, right-hand cutting, DIN 340, ~ 10D, cyl, Shank, tolerance h8, [Guhring No. 396] Application: Stainless Steel (Equivalent Acceptable brands: Stock, Dormer, OSG only)	
Sr.#	Dia(mm)	Qty
1	1.0	30
2	1.1	10
3	1.2	10
4	1.3	10
5	1.5	10
6	1.6	30
7	1.8	10
8	1.9	10
9	2.0	10
10	2.1	10
11	2.2	30
12	2.3	10
13	2.4	20
14	2.5	10
15	2.7	10
16	2.8	30
17	2.9	10
18	3.0	10
19	3.1	10
20	3.2	10
21	3.3	30

HSCO DRILLS

22	3.4	10
23	3.5	10
24	3.6	30
25	3.8	10
26	3.9	30
27	4.0	10
28	4.1	10
29	4.2	20
30	4.5	20
31	4.8	30
32	4.9	10
33	5.0	10
34	5.1	10
35	5.2	30
36	5.4	10
37	5.5	10
38	5.8	10
39	5.9	10
40	6.0	10
41	6.2	30
42	6.5	30
43	6.7	10
44	6.8	10

HSCO DRILLS

45	7.0	10
46	7.2	30
47	7.4	10
48	7.5	10
49	7.6	10
50	7.7	10
51	7.8	20
52	7.9	10
53	8.0	10
54	8.2	10
55	8.3	10
56	8.5	10
57	8.6	20
58	8.8	20
59	8.9	30
60	9.0	20
61	9.1	20
62	9.2	10
63	9.3	10
64	9.5	10
65	9.6	10
66	9.7	20
67	10.0	10

HSCO DRILLS

68	10.2	a°
69	10.5	10
70	11.0	10
71	11.5	10
72	12.0	10
B	HSCO Twist Drill with Reinforced Straight shank, ~ 5xD, tolerance h8, [Guhring No. 511] Application: Stainless Steel (Equivalent Acceptable brands: Stock, Dormer, OSG only)	
Sr.#	Dia(mm)	Qty
73	2.0	30
74	2.1	10
75	2.3	10
76	2.4	10
77	2.5	30
78	2.6	20
79	2.8	10
80	2.9	10
81	3.0	30
82	3.1	10
83	3.2	10
84	3.3	30
85	3.4	20
86	3.5	30
87	3.9	10
88	4.0	30

HSCO DRILLS

89	4.2	20
90	4.3	20
91	4.4	10
92	4.5	10
93	4.7	10
94	4.8	10
95	4.9	10
96	5.0	30
97	5.1	30
98	5.2	30
99	5.3	10
100	5.4	10
101	5.5	30
102	5.6	10
103	5.8	10
104	5.9	10
105	6.0	20
106	6.1	10
107	6.3	10
108	6.4	10
109	6.5	10
110	6.6	10

HSCO DRILLS

111	6.8	30
112	6.9	10
113	7.0	10
114	7.1	10
115	7.2	10
116	7.3	10
117	7.4	10
118	7.5	10
119	7.6	10
120	7.7	10
121	7.8	10
122	7.9	10
123	8.0	10
124	8.1	10
125	8.2	10
126	8.3	10
127	8.5	10
128	8.6	20
129	8.8	10
130	8.9	10
131	9.0	20
132	9.1	10

HSCO DRILLS

133	9.4	10
134	9.5	20
135	9.6	10
136	9.9	10
137	10.0	10
138	10.1	10
139	10.2	10
140	10.4	20
141	10.5	20
142	10.6	10
143	10.8	10
144	11.0	20