

BUTTERFLY VALVES

Sr#	Description	Qty
1	Butterfly Valve (Wafer type: Application: HVAC System. Media: Clean Water. Nominal Pressure: PN-16. Shaft: SS. Disc: SS 304. Seat EPDM. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent Flange Type: Raised Face. Material of Construction: Ductile Iron body. Hydrostatic Test Pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range: 5 to 80 °C. Type: Lever operated for size less than 6", and worm gear operated for size greater than 6" with position indicator and switch for open and close status. Size: 5"Ø, EU, USA, Japan or Equivalent.)	11
2	Butterfly Valve (Wafer type: Application: HVAC System. Media: Clean Water. Nominal Pressure: PN-16. Shaft SS. Disc: SS 304. Seat EPDM. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent Flange Type: Raised Face. Material of Construction: Ductile Iron body. Hydrostatic Test Pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range: 5 to. 80 °C. Type: Lever operated for size less than 6", and worm gear operated for size greater than 6" with position indicator and switch for open and dose status. Size: 4"Ø, EU, USA, Japan or Equivalent)	09
3	Butterfly Valve (Wafer type: Application: HVAC System. Media: Clean Water. Nominal Pressure: PN-16, Shaft SS. Disc: SS 304. Seat: EPDM. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent. Flange Type: Raised Face. Material of Construction: Ductile Iron body. Hydrostatic Test Pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range: 5 to 80 °C. Type: Lever operated for size less than 6'1 2 3 4 5 6, and worm gear operated for size greater than 6" with position indicator and switch for open and close status. Size: 3"Ø, EU, USA, Japan or Equivalent)	24
NOTES: Manufacturers: Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran , Crane Valves, CEPEX, KSB Germany.		