

## Y STRAINER

Sr#	Description	Qty
1	<b>Strainer Y</b> (Application: HVAC System. Media: Clean Water. Nominal Pressure: PN16. Type: Y-Type Bolted Cover. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent Flange type: Raised Face. Material of Construction: Cast Iron. Screen: S.S Screen 1.5mm perforation size. Hydrostatic test pressure, pressure/temperature rating: To be specified by the manufacturer. Temperature Range: 5 to 80 °C. Size: 5"Ø., EU, USA, Japan or Equivalent.)	02
2	<b>Strainer Y</b> (Application: HVAC System. Media: Clean Water, Nominal Pressure: PN16. Type: Y-Type Bolted Cover. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent Flange type: Raised Face. Material of Construction: Cast Iron. Screen: S.S Screen 1.5mm perforation size. Hydrostatic test pressure, pressure/temperature rating: To be specified by the manufacturer. Temperature Range: 5 to 80 °C. Size: 4" Ø, EU, USA, Japan or Equivalent)	02
3	<b>Strainer Y</b> (Application: HVAC System. Media: Clean Water. Nominal Pressure: PN16. Type: Y-Type Bolted Cover. End Connection: Flanged Connection/Flanged to DIN-2633 or Equivalent. Flange type: Raised Face. Material of Construction: Cast Iron. Screen: S.S Screen 1.5mm perforation size. Hydrostatic test pressure, pressure/temperature rating: To be specified by the manufacturer. Temperature Range: 5 to 80 °C. Size: 3" Ø., EU, USA, Japan)	14
<b>NOTES:</b>  <b>Manufacturers</b> : Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran, Crane Valves, CEPEX, KSB Germany.		