

Sr. #	Item Description	A/U	Qty.
1	Pneumatic Straight Way Globe Valve (DN: 50, PN: 100, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), LOX compatible, Air Supply 6 bar, Air failure position: Closed, Mode of operation: Close or Open, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
2	Pneumatic Straight Way Globe Valve (DN: 50, PN: 40, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), Material: 1.4308, LOX compatible, Air Supply 6 bar, Air failure position: Closed, Mode of operation: Close or Open, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
3	Pneumatic Straight Way Globe Valve (DN: 50, PN: 60, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), Material: 1.4308, LOX compatible, Air Supply 6 bar, Air failure position: Closed, Mode of operation: Close or Open, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
4	Globe Valve (DN: 50, PN: 15, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), LOX compatible, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
5	Globe Valve (DN: 50, PN: 100, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), LOX compatible, Ends: Flanged)	No	1
6	Globe Valve (DN: 50, PN: 60, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), LOX compatible, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
7	Globe Valve (DN: 50, PN: 40, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), Material: 1.4308, LOX compatible, Ends: Flanged, Model: 941V, Phonix Armaturen-werke Bergel G.M.B.H, Germany)	No	1
8	Globe Valve (DN: 25, PN: 100, Body Form: Straight, Service temperature (-200 deg cen to 100 deg cen), LOX compatible, Ends: Flanged)	No	1
9	Pressure Relief Valve(Straight-way) (DN: 50, PN: 100, Adjustment Range: 95 to 110 bar, Connections: Flanges, Service Temperature: -200deg cen to +100deg cen, LOX compatible)	No	1
10	Pressure Relief Valve(Straight-way) (DN: 25, PN: 100, Adjustment Range: 95 to 110 bar, Connections: Flanges, Service Temperature: -200deg cen to +100deg cen, LOX compatible)	No	1
11	Pressure Relief Valve(Straight-way) (DN: 25, PN: 60, Adjustment Range: 55 to 65 bar, Connections: Flanges, Service Temperature: -200deg cen to +100deg cen, LOX compatible)	No	1
12	Pressure Relief Valve(Straight-way) (DN: 50, PN: 40, Adjustment Range: 35 to 45 bar, Connections: Flanges, Service Temperature: -200deg cen to +100deg cen, LOX compatible)	No	1

13	Pressure Relief Valve(Straight-way) (DN: 50, PN: 20, Adjustment Range: 15 to 25 bar, Connections: Flanges, Service Temperature: -200deg cen to +100deg cen, LOX compatible)	No	1
14	Flow Meter (Flow Rate: upto 10 liter/sec, DN: 50, PN: 100, Service Temperature: -200 deg cen to 100, LOX compatible)	No	1
15	Flow Meter (Flow Rate: upto 10 liter/sec, DN: 50, PN: 40, Service Temperature: -200 deg cen to 100, LOX compatible)	No	1
16	pressure Transducer (Pressure: 0-100 bar, Service temperature: -200 deg cen to 100 deg cen, LOX compatible, Omega)	No	1