

Origin: Australia, Canada, China, USA and European Countries

Sr	Description	Quantity	
1	12" dia milled tooth tricone roller rock bit with 6-5/8" API regular pin (IADC 321)	02	Nos.
2	15" dia milled tooth tricone roller rock bit with 6-5/8" API regular pin (IADC 321)	02	Nos.
3	Heavy duty swivel hoist plug with 2-3/8" API IF pin	06	Nos.
4	HQWL inner tube knuckle head	06	Nos.
5	HQWL Hoisting plug	06	Nos.
6	HQWL outer tube wrench	06	Nos.
7	HQWL inner tube wrench	06	Nos.
8	Over size HW impregnated casing shoe with outer dia 140mm	06	Nos.
9	Heavy duty hoist plug for HW casing	06	Nos.
10	Safety foot clamp replacement jaws set for HW casing (2 Pcs / Set)	06	Sets
11	Drill Collar 3 meter long with: Outer Dia: 4-1/8 inches Bore Size: 1-3/4 inches	04	Nos.
	Joint Type (Pin & Box): 2-3/8" API IF No. of flats for break out wrench: 04 Nos. on both ends		
12	Spiral hard faced welded blade stabilizer for hole size 5-1/8" with: Blade Length: 18 inches Quantity of Blades: 03 Nos. Mid Body Length: 1.50 meters Mid Body Wall Thickness: 8.8mm Mid Body Outer Dia: 3-1/2 inches Mid Body Inner Dia: 1-3/4 inches Joint Type (Pin & Box): 2-3/8" API IF No. of flats for break out wrench: 04 Nos. on both ends	06	Nos.
13	Spiral hard faced welded blade stabilizer for hole size 4-1/2" with: Blade Length: 18 inches Quantity of Blades: 03 Nos. Mid Body Length: 1.50 meters Mid Body Wall Thickness: 8.8mm Mid Body Outer Dia: 3-1/2 inches Mid Body Inner Dia: 1-3/4 inches Joint Type (Pin & Box): 2-3/8" API IF No. of flats for break out wrench: 04 Nos. on both ends	12	Nos.

- Note:**
1. Chinese manufacturers should be certified from API/IADC and these certificates must be provided with quotations.
 2. Quotations should clearly show Make/Origin of quoted items.
 3. Technical literature showing complete specifications should be provided with quotations.