Sr. No.	Description/Specifications/Cat/Part No. of Scientific/Technical/Administrative Stores.	Qty Requ ired
1	2	3
01	X-ray Generator for XRF. XDF Series Model # XDF60P4 Manufacturer: WIZMAN, china. Manufacturer's brochure attached.	One
	Specifications:  Input Voltage: 180VAC- 264VAC Standard, Single Phase Output Voltage: 60 kV Adjustable	,
•	<ul> <li>(Positive Polarity)</li> <li>Output Current: 67 mA Adjustable</li> <li>Output Power: 4Kw</li> <li>Filament Power: 12VDC Voltage,</li> </ul>	
	12 Ampere max. Current. (Adjustable Voltage and Current) Detachable High Voltage and Filament separate Cables (3 Meters	
en	each) with connectors on both sides for connection with x-ray tube.  • Ethernet and RS-232 Digital interface implemented with 12 bits	10 <b>*</b>
7	of resolution. A VB GUI interface will be provided. All software configurable features like Arc Trip count, Arc Quench Time, Arc re-	,

ramp time etc, must be available. (As mentioned in the attached manufacturer's brochure).

Factory Acceptance Test (FAT): Supplier will arrange FAT of the equipment and hands on training of one person at manufacturer's site. Its financial impact may be mentioned separately in the quotation.