

## Quotation for Three groups of Pasta processing line

Makarna işleme hattının üç grup için Teklif

Capacity: 680-750kg/h

Kapasite: 680-750 kg/h

Sample picture:

Gorsel resimler:



Price List: fiyat listesi

Equipment name Malzeme ismi	Motor power Motor gucu	QTY. adet	Unit Price (USD) Brim fiyat	Sub-Amount (USD) tutar
ZK600 Flour mixer Un karistirici	4KW/set	3		
Screw conveyor Vidali konveyor	1.1KW/set	3		
ZK100 single screw extruder Makarna cekme makinasi	45KW/set	3		
Pulling & cutting machine Çekme ve kesme makinasi	1.1KW/set	3		
Cooler conveyor Sogutucu konveyor	1.1KW	1		
Hoister tasiyici	0.55KW	1		
ZKKX-9 Electric oven (5 layers)First Baking 5 kademe ilk elektrikli kurutucu	160KW	1		
Hoister tasiyici	0.55KW	1		

ZKKX-9 Electric oven (5 layers)Second Baking 5 kademe ikinci elektrikli kurutucu	160KW	1		
Cooler conveyer Sogutucu konveyir	1.1KW	1		
Expenses from our factory to Qingdao port China Çindeki Lokal tasima ucreti		Three 40GP containers		
Freight from Qingdao port, China to Mersin port, Turkey Çinden Türkiyeye navlun ucreti		Three 40GP containers		
Insurance for All risks sigorta		USD		
<b>Total Amount</b> <b>Toplam tutar</b>				

**Remarks:**

1. Delivery time and terms:
2. Payment term: of the total value should be paid by T/T in advance as the deposit, the balance % to be paid by T/T before shipment from the seller's company.  
Odeme sekli , % pesin , kalan bakiye % sevkiyat yapilmadan once .
3. Port of Loading: yukleme limani ,
4. Packing: In bulk in container. Paketleme , konteynir ici yukleme.
5. Quality Guarantee Terms: Quality guarantee term is for 12 month. Kalite Garantisi 12 ay.
6. Above price is available still . yukaridaki fiyatlar kadar gecerlidir.

**List of Spare Parts For your reference**

**Yedek parca listesi**

Part name Parca ismi	Durable years Calisma suresi	Price/1piece Parca fiyatı	Qty. Per year Yillik adet
Die head Lokma basligi	1year – 1 yıl		1
Rotary cutter Döner kesici	6months – 6 ay		2
Traction cutting knife Kesici bicaklar	4months – 4 ay		3
Heating tube Isıtıcı boru	3-5years – 3-5 yıl		1
A year of wearing parts consumption Bir yıllık yedek parça tutarı		USD	

## Equipments Description

### 1. ZK600 Flour mixer

**Description:** The flour mixer is widely used in restaurant, hotel, mess hall, food processing factory and other catering units. This machine is durable and easy to be operated. It is suitable for mixing all kinds of flour.



#### Technical Parameter:

Model	ZK600
Power	4KW
Capacity	30-40kg/once; 250-300kg/h
Dimension	0.9m*0.6m*1.1m

### 2. Screw conveyor

**Description:** Stainless steel structure, especially the parts in contacting with the raw material or products;

It can work either horizontal or at any angle. The materials are conveyed in a sealed stainless steel. Roller to the feeding hopper of extruder without leaking, dust pollution. The conveying speed can be controlled freely. The conveying quantity is even and stable. Easy cleaning and operation; run stably.



#### Technical Parameter:

Power	1.1KW
Dimension	2m*0.6m*2.5m

### 3. ZK100 Single screw extruder

**Description:** Series of singles screw extruder are consisting of feeding system, extruding system, cutting system, heating system, gearing system and controlling system, Feeding system, driving system and cutting system adopt inverter speed controlling, strong motility, steady running, Screw, barrel, moulds adopt circulation cooling system to keep temperature steady during working.



**Technical Parameter:**

Model	ZK100 single screw extruder
Power	45KW
Capacity	230-280kg/h
Dimension	2m*1.6m*2.1m

**4. Pulling & cutting machine**

**Description:** Pulling and cutting short pasta.



**Technical Parameter:**

Power	1.1KW
Dimension	2.3m*0.8m*1.1m

**5. Cooler conveyor**

**Description:** Cooling the pasta and convey pasta to next machine.



**Technical Parameter:**

Power	1.1KW
Dimension	5m*0.62m*1.3m

**6. Hoister**

**Description:** Convey pasta from pulling & cutting machine into oven.



**Technical Parameter:**

Power	0.55KW
Output	300-500kg/h
Dimension	3.4*0.6*2.5m

**7. Electric oven for baking**

**Description:** Infrared radiation heating tube heating, heating and cooling rapidly, thermal inertia small, high thermal efficiency. Installation of hot air circulation device, make the oven temperature warming faster, saving energy, saving time



**Technical Parameter:**

Power - elektrik tüketimi	160KW
Heating temperature- ısıtma sıcaklığı	60-160 degrees
Output – urun çıkışı	300-500KG/h
Dimension- ebatlar	9.8m*1.45m*2.38m

**Delivery site:**

