

Sr. No.	Description	Qty Required (Nos.)
1	2	3
01	Pressure Gauge Wetted Part Material: PTFE Body Material: PTFE/PVDF Dial Size: 4 inch Connection: NPT 15 (Male) Pressure Range: 0-160 PSI Temperature Range 0-150 °C	08
02	Adjustable Pressure Relieve Valve Body Material: PVDF Diaphragm material: EPDM or PTFE Pressure setting range: 0.5-5 bar Opening pressure: approx. 0.5 bar Fluid Temperature range: 0-100 °C Connections: union fusion sockets ND 20.	10
03	Pressure Transmitter with display Wetted Part Material: PTFE Pressure Range: 0-160 PSI Temperature Range 0-180 °C Connection: NPT 25 (Male) Input supply: 24 Vdc Output: Analog output: 4-20 mA Relay Output	02
04	Ultrasonic Level Transmitter with Display Sensor Body: PTFE/PVDF Range: 0-3 Meter Resolution : 3 mm Minimum Tank Diameter: 900 mm Input supply: 24 Vdc Output: Analog output: 4-20 mA Relay Output:	02
05	Gas flow Transmitter with Display Model : C5 EX1 (ASAMETER with microprocessor Transmitter, Local Display and alarm) Wetted part Material: Hastelloy "C" Indicator Housing: Inox AISI 316L Connection : Screwed NPT 15 (Female) Flow Range: 1.2 m3 to 12 m3 Pressure Range: 1 Bar to 4 Bar Analog output: 4-20 mA Total volume display/Transmit function Or Equivalent	03

Note: Required Spares and operational manuals may please be provided.