SPECIFICATIONS SHEET

PES/BP2-18-108(1UY)

5/	Description	ge-02/02
No		Qty
1.	Spin Coater	(Nos
	Model: Spin Coater SCS 6800 Programmable or equivalent,	UI
	Rotating Speed: 0-10000 rpm (Programmable).	
	Accuracy: < ±1% error across the full range,	
	Display: Yes keypad and LCD Display on the front panel, Bowl Size Programmable: 8 in/20.3 cm,	9 1
	Power: 240VAC, 50/60Hz, Dwell Time: 0 to 999 seconds in 1 second increments,	
	Dimensions (WxDxH): 3.25x18x10.8 in/ 33.7x45.7x27.4 cm,	
	Acceleration/ Deceleration: 0.1-30	17.6
	Dispense Time: 10to30 seconds in 0.1 second increments	
2.	External Vacuum Pump:	01
	Accessories:	01
	i. Vacuum Chucks	
	a. Type CS: Flat Surface Cross and Scroll	
	b. Type H: O-ring Vacuum-Holding	
	c. Type L: O-ring Vacuum-Holding	
	d. Type Pedestal: Non-Vacuum	
	ii. Foot Pedal	
	iii. Software	
1	Note:	-
	 In addition to total price, the price of each and every part/ module/ accessory/ 	
	unit etc. included in the quantities must be a served by party module/ accessory/	
	unit etc. included in the quotation must be quoted separately and clearly.	
	Warranty: 1-Year complete warranty.	
	Prospective supplier:	
	https://scscoatings.com/equipment/spin-coating-systems/6800-spin-coaters/	