## ELECTRIC MOTORS 3 (PHASE INDUCTION MOTORS)

Sr#	Description	Qty
	3-Phase Induction Motors	
	Rated Voltage: 3 Phase, 380-415V	
	Ambient Temperature: 50°C	
	Frequency:50 Hz	
	• Power Factor $\geq 0.85$	
	• Speed Tolerance ±1%	
	Insulation Class: H	
	• SF: 1.15,	
	Duty: Continuous	
	Ingress Protection: IP 55	
	TEFC, High Efficiency Copper Wound	
	Make: Baldor Reliance / ABB / Siemens / WEG or Equivalent	
1	3 Phase Induction Motor	One
	• Rated Power: 125 HP / 93 kW, 177 A, 1485 RPM	
	Frame Size: NEMA 444T, B3 Mounting	
	Connection Box: Left From Drive End	
2	3 Phase Induction Motor	2
	<ul> <li>Rated Power: 30 HP / 22 kW, 42 A, 2930 RPM</li> </ul>	
	Frame Size: NEMA 284T, B3 Mounting	
	Connection Box: Left From Drive End	
3	3 Phase Induction Motor	One
	<ul> <li>Rated Power: 10 HP / 7.5 kW, 13.7 A, 2900 RPM</li> </ul>	
	Frame Size: NEMA 215T, B3 Mounting	
	Connection Box: Left From Drive End	
4	3 Phase Induction Motor	2
	<ul> <li>Rated Power: 5 HP / 3.7 kW, 7.4 A, 2900 RPM</li> </ul>	
	Frame Size: NEMA 184T, B3 Mounting	
	Connection Box: Left From Drive End	
5	3 Phase Induction Motor	One
	<ul> <li>Rated Power: 3 HP / 2.2 kW, 4.3 A, 2900 RPM</li> </ul>	
	Frame Size: NEMA 182T, B3 Mounting	
	Connection Box: Left From Drive End	
	es: echnical literature of the offered items must be provided with the quotation. ake and country of origin of the offered items should be mentioned in the q	