

2-14

S.No.	Part Number	Description	Total Qty.
1	90106	DB-25 connector and cable for VS4095/5 90 connection to serial port	2
2	10S212	Standard 7.62x7.62cm plain paper roll for VS4095/5 90, 6.86mm thickness, from Keltron	10
3	10S220	Two color (Red / Black) ribbon, snap-in cassette cartridge for VS4095/5 90, from Keltron	2
4	31D1243	Internally powered Time / Date stamp for VS4095/5 90, from Keltron	1
5	ACPS-610E	Addressable (5 to 14 SLC addresses) auxiliary power supply and battery charger, 6A / 10A output shared in 4 circuits, charges 12 to 200 AH batteries, input 240VAC / 50Hz / 2.5A	1
6	ADP-4B	Annunciator Dress Panel-4B (black), The ADP-4B hinge-mounts to a CAB-4 Series cabinet, One to four modules mount directly to threaded studs on the ADP-4B	1
7	AMPS-24E	Addressable (5 SLC addresses) main power supply and battery charger for NFS2-3030E, two 24 VDC outputs, charges 7 to 200 AH batteries, input 240VAC / 50Hz / 2.5A	1
8	BMP-1	Blank module plates to cover unused positions in dress plate	5
9	BP2-4	Main battery panel for NFS2-3030E, holds up to two 26AH batteries	1
10	CB-1	Chassis bridge, provides a bridge between CHS series chassis	3
11	CHS-4	Mounting chassis for up to 4 modules	1
12	CHS-4L	Low-profile mounting chassis for up to 4 modules	1
13	CHS-6	Mounting chassis for up to 6 modules	4
14	CHS-BH	Battery mounting chassis, holds up to two 12AH batteries on a CHS-PS	1
15	CHS-M3	Mounting chassis for CPU2-3030D	1
16	CHS-PS	Chassis for mounting ACPS-610E in row 1, 2, or 3 of the CAB-4 series enclosure	1
17	CPU2-3030D	Central processing unit for NFS2-3030E, includes 640-character backlit LCD display, QWERTY programming and control keypad	1
18	DP-1B	Blank dress panel, provides dead-front panel for unused tiers	2
19	DP-DISP	Dress panel for top row in cabinet with CPU2-3030D installed	1
20	DR-D4	Door assembly, LEXAN window, 4 tiers, Black	1
21	HS-NCM-W	High speed network communications module, connects two nodes up to 914.4m in point-to-point fashion, 12Mb transmission rate with electrical isolation	2
22	ISO-6	SLC fault isolator module for 6 circuits	7
23	LCM-320	Loop control module, provides one SLC	2
24	LEM-320	Loop expander module, expands an LCM-320 for an additional SLC	2
25	MODBUS-GW	Provides a communication link between networks that use the Modbus/TCP communication protocol and Fire Alarm Control Panels (FACPs) resident on an NFN network	1

3/4

26	NFN-GW-EM-3	Embedded NOTI•FIRE•NET™ gateway, includes PC board, NUP to NUP cable (75577), USB cable (75665) and NFN configuration	1
27	P40-KITB	CAB-4 series mounting kit for VS4095, includes chassis, hinged dress plate, and mounting hardware	1
28	RPT485 isolator/repeater	For isolation of EIA-485 lines in the NFS2-3030 panel	2
29	SBB-D4	Backbox assembly, 4 tiers, Black	1
30	SCE-8	Smoke Control Expander Module, expands the SCS-8 switches to 16	1
31	SCS-8	Smoke Control Master Module, Eight switches expandable to 16 with SCE-8	1
32	SCS-8L	Smoke Control Lamp Driver Master Module, Eight switches	1
33	SEISKIT-CAB	Seismic mounting kit for NFS2-3030E mounted in CAB-4 series enclosures, includes battery bracket for two 26 AH batteries	4
34	TR-D4	Accessory semi-flush-mount trim ring, 4 tiers, Black	1
35	VS4095/5 90	Impact printer, panel-mount, 40 column, EIA-232 interface, 24 VDC, two-color (Red / Black), without security cabinet, from Keltron	1
36	WC-2	Wire channel, provides a pair of wire trays to neatly route wiring between CHS chassis	3
37	Commissioning Software	Software with license for configuration of NFS2-3030 panel	1
38	POL-100	Loop test tool	1
39	POL-100-ACC	Accessory belt for POL-100	1
40	17021	Keys for NBG-12LX, set of two	2
41	887/EOL	End of line box for SS-LDN-68-155-500	2
42	B224BI-IV	Detector base, provides isolation, Ivory	10
43	B501-WHITE-BP	Detector base, Bulk pack, 10 bases	4
44	BG12TR	Trim ring for NBG-12LX	2
45	DNRW	Watertight intelligent non-relay photoelectric low flow duct smoke detector housing	1
46	DST1.5	Metal sampling tube duct widths up to 1 ft. to 2 ft. (0.3 to 0.6 m), for DNRW	2
47	ETX	Metal exhaust tube duct, width 1 ft. (0.3 m), for DNRW	2
48	FCM-1	Intelligent Addressable Control Module, Configured for Class A or Class B NAC, Requires separate power for horns, strobes or speakers	10
49	FDM-1	Addressable (2 SLC addresses) monitor module, supervises two independent Style B (Class B) circuits, capable of monitoring normally open contact fire alarm and supervisory devices; or either normally open or normally closed security devices, includes two 47K ohm EOL resistors	10
50	FDRM-1	Two individual relay control modules and two Class B monitor modules	12
51	FM101	Addressable Mini Module with FlashScan; Supervises a Class B circuit of dry- contact devises.	5

4/4

52	FMM-1	Addressable monitor module, supervises either a Style D (Class A) or Style B (Class B) circuit of dry-contact input devices, includes a 47K ohm EOL resistor for Style B circuit	15
53	FSP-951	Addressable smoke detector without base, low profile photoelectric sensor, White	20
54	FSP-951R	White, low-profile intelligent photoelectric sensor, remote test capable, for DNRW	2
55	FST-951	Addressable heat detector without base, low profile 57°C thermal sensor, White	10
56	FST-951H	Addressable heat detector without base, low profile 88°C thermal sensor, White	5
57	ISO-X	SLC fault isolator module	20
58	NBG-12LX	Addressable pull station with key locking, dual action, Red	5
59	P2RL	Indoor wall horn / strobe, Red, 2-wire	5
60	PLP-42-S	SLC surge protector, 30V / 7A, from Emerson	2
61	SB-10	Surface backbox for NBG-12LX, metal	3
62	SBBRL	Wall surface backbox for horn / strobe, Red	3
63	SL2DIN-36/2A	DC surge protector, 2 pair / 36V clamping / 2A, from Novaris	2
64	SMB500	Surface backbox for monitor modules	10
65	SMB600	Surface mounting kit, for detectors	5
66	SS-LDN-68-155-500	Digital linear heat detection cable, 68°C, twisted pair with Nylon extrusion, 500m reel, from SystemSensor	1
67	TR-2	Wall trim ring for horn / strobe, Red	2
68	DR-A4B	Door assembly, solid door, one tier, BLACK, for CAB-4 A Size cabinet	1
69	SBB-A4	Backbox assembly, one tier, BLACK, for CAB-4 A Size cabinet	1
70	TR-A4	Accessory semi-flush-mount trim ring, one tier, for CAB-4 A Size cabinet	1