

EXPANSION JOINT

Sr.#	Item Description	A/U	Qty.
1	<p>Expansion Joint SS (Size 8° dia, Application HVAC System. Nominal pressure: PN16. Type: Expansion joint single sphere, Floating flanges. End connection: Flanged connection/Flanged to DIN-2633 or equivalent Flange type: Raised face. Material of Construction: Rubber expansion Joint Material of Flange: Stainless Steel</p> <p>Hydrostatic test pressure, pressure/temperature rating, material specification: To be specified by the manufacturer, Axial Compression: 25mm, Axial Elongation: 14mm, Transverse deflection: 22mm, Angular deflection 15°, Temperature range (05C° to 80CD),(USA/EU/Japan)</p>	No	8
2	<p>Expansion Joint (Application HVAC System. Function: protection. Nominal pressure: PN16. Type: Expansion joint single sphere, Floating flanges. End connection: Flanged connection/Flanged to DIN-2633 or equivalent. Flange type: Raised face. Material of Construction: Rubber Expansion Joint. Hydrostatic test pressure, pressure/temperature rating material specification: To be specified by the manufacturer. Size: 6"ø, EU, USA, Japan or Equivalent.)</p>	No	30
3	<p>Expansion Joint (Application HVAC System. Function: protection. Nominal pressure: PN16. Type: Expansion joint single sphere, Floating flanges. End connection: Flanged connection/Flanged to DIN-2633 or equivalent. Flange type: Raised face. Material of Construction: Rubber Expansion Joint Hydrostatic test pressure, pressure/temperature rating material specification: To be specified by the manufacturer. Size: 5" ø, EU, USA, Japan or Equivalent)</p>	No	15
<p><u>Recommended Manufacturers /if any):</u></p> <p>Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran valves, CEPEX, KSB Germany, Euroguarco</p>			