

No.	Product	Material	Description	Qty Pcs
1	Yokogawa Pressure Transmitters	SS 316	Type: Diaphragm sealed gauge pressure transmitter Range: -1000 to 4000 mbar (g) Accuracy: 1 mbar Max. Fluid Temperature : 150 Process connection: NPS 2" flanged ANSI 150 Integral digital indicator with the range setting switch Input: 2 wire loop powered 24 VDC Output: 4 to 20 mA digital communication (HART Protocol) Calillary length: 5m Make: Yokogawa	4
2	Yokogawa Teflon Shield F9347YA	SS 316	Teflon protective shields for PT Model EJA438W (NPS2) Protective shield part No.: F9347YA Make: Yokogawa	10
3	PH Transmitters	SS 316	Type: Industrial pH Meter with transmitters pH measurement Range: 0-14 pH (both acid and base , fluoride media) Max. Fluid Temperature: 80°C Electrode cleaning attachment: Mechanical (brush) Process connection : NPS 3", Union Accuracy: ±0.1 pH Enclosure Class: NEMA-4X, 1/2" conduit connection Input: 2 wire loop powered 24 VDC Output: 4 to 20 mA with digital communication (HART Protocol) Make: Yokogawa, Rosemount, E&H or equivalent	4
4	Spare PH Electrodes	SS 316	Spare Electrodes for pH transmitter Fluoride resistant Make: Yokogawa, Rosemount, E&H or equivalent	10