





Pressure: 320 bar Pump capacity: 25 – 50 l/min Hydraulic couplings (input, output): M 18 x 1.5



Load	Hole pattern	flange B	connection	Torque	Moment of	Self
capacity	(kg)	(mm)	C x A* (mm)	(Nm)	deflection max.	weight
4500	□ 140	84 x 30	84 x 30	850	3000	40

WITH FLANGE AND 4 OIL DUCTS (incl. fittings)

Pressure: 320 bar Pump capacity: 25 – 60 l/min Hydraulic couplings (input, output): M 18 x 1.5





Load	Hole pattern	flange B	connection	Torque	Moment of	Self
capacity	(kg)	(mm)	C x A* (mm)	(Nm)	deflection max.	weight
4500	□ 140	84 x 30	84 x 30	850	3000	26
4500	□ 140	84 x 30	84 x 30	850	3000	26

** vertical connection in addition for the attachment

WITH FLANGE UP TO 4500 KG LOAD CAPACITY (incl. fittings)

Pressure: 320 bar Pump capacity: 25 – 60 l/min Hydraulic couplings (input, output): M 18 x 1.5





Load	Shaft-Ø B	connection	Torque	Moment of	Self
capacity	(kg)	(mm)	C x A* (mm)	(Nm)	deflection max.
4500	59	84 x 30	850	3000	26
4500	62	84 x 30	850	3000	26
4500	63	84 x 30	850	3000	26
4500	68	84 x 30	850	3000	26
4500	68	84 x 30	850	3000	28
4500	69	84 x 30	850	3000	26

** steel motor-head

WITH SHAFT UP TO 4500 KG LOAD CAPACITY (incl. fittings)

Pressure: 320 bar Pump capacity: 25 – 60 l/min Hydraulic couplings (input, output): G 3/8"



Load	Shaft-Ø B	connection	Torque	Moment of	Self
capacity	(kg)	(mm)	C x A* (mm)	(Nm)	deflection max.
3000	49.5	60 x 25	450	1750	24

Hydraulic couplings-in: G 3/8"

Hydraulic couplings-out: G 1/4"

WITH SHAFT UP TO 3000 KG LOAD CAPACITY (incl. fittings)