

**DATA SHEET FOR TRUCK
UNLOADING PUMPS (P-4003 A/B)**

1FOR : Iran National Copper Industry Co.

2SITE: Bandar Abbas Sulfuric Acid Transport Terminal Project (EPC&O)SREVICE Sulfuric Acid

3No. of Req'd: 2Service: 2/ Stand by :PUMP TYPE= VS4

4NOTES : INFORMATION BELOW TO BE COMPLETED: ☒ BY PURCHASER ☐ BY MANUFACTURER ☐ BY MANUFACTURER OR PURCHASER

5

DATA SHEETS

ITEM NO.

ATTACHED

ITEM NO.

ATTACHED

ITEM NO.

ATTACHED

NO.

DATE

BY

PUMP

P-4003 A/B

MOTOR

MP-4003 A/B

6

7

8

9APPLICABLE OVERLAY STANDARD(S) : API 610 - 10TH

10

OPERATING CONDITIONS

LIQUID

11FLOW, NORMAL 60 (m³/h) RATED 75 (m³/h)

12MINIMUM (m3/h)

13SUCTION PRESSURE MAX / RATED 0 / (barg)

14DISCHARGE PRESSURE 4 (barg)

15DIFFERENTIAL PRESSURE 4.0 @ 50 m3/hr & 3.5 @ 75 m3/hr (bar)

16DIFF. HEAD 22 (m) NPSHA 4.5 (m)

17PROCESS VARIATIONS

18STARTING CONDITIONS OPEN VALVE

19SERVICE: ☐ CONT ☒ INTERMITTENT (STARTS/DAY)

20☐ PARALLEL OPERATION REQ'D

21

SITE DATA (NOTE 5)

22LOCATION: (5.1.30)

23☐ INDOOR ☐ HEATED ☒ OUTDOOR ☐ UNHEATED

24☒ ELECTRICAL AREA CLASSIFICATION

25ZONE GR TC Safe

26☐ WINTERIZATION REQ'D ☐ TROPICALIZATION REQ'D

27SITE DATA

28☒ ALTITUDE 16.5 (m) BAROMETER 1 (bar)

29☒ RANGE OF AMBIENT TEMPS:MIN. / MAX. 4 / 47.6 (°C)

30☒ RELATIVE HUMIDITY:MIN. / MAX. 27 / 95 (%)

31UNUSUAL CONDITIONS: (5.1.30) ☒ DUST ☐ FUMES

32☒ OTHER

33

34

35

DRIVER TYPE

36☒ INDUCTION MOTOR ☐ STEAM TURBINE ☐ GEAR

37☐ OTHER

38

MOTOR DRIVER

39☐ MANUFACTURER

40(kw) (r/min)

41☐ FRAME ☒ ENCLOSURE IP 55

42☐ HORIZONTAL ☒ VERTICAL ☒ SERVICE FACTOR 1

43☒ VOLTS / PHASE / HERTZ 400 / 3 / 50

44☒ TYPE Induction, Squirrel Cage

45☒ MINIMUM STARTING VOLTAGE (6.1.5) 80%

46☒ INSULATION F ☒ TEMP. RISE B

47☐ FULL LOAD AMPS

48☐ LOCKED ROTOR AMPS

49☒ STARTING METHOD VFD

50☐ LUBE

51BEARINGS (TYPE / NUMBER) :

52☐ RADIAL /

53☐ THRUST /

54☐ VERTICAL THRUST CAPACITY

55UP (N) DOWN (N)

56

57

58

LIQUID TYPE OR NAME Sulfuric Acid

☒ HAZARDOUS ☐ FLAMMABLE

MIN. TEMP.	NORMAL. TEMP.	MAX. TEMP.
5	45	
VAPOUR PRESS . (barA)	0.01	0.01
RELATIVE DENSITY (SG):	1.868	1.84
VISCOSITY (cp)	38.87	12

SPECIFIC HEAT, Cp

☐ CHLORIDE CONCENTRATION

☐ H₂S CONCENTRATION WET

CORROSIVE / EROSIIVE AGENT

MATERIALS NOTE 2

☒ MIN DESIGN METAL TEMP: -4 (°C) MATERIAL CLASS:

☒ CASE CF-8M CASE GASKET TEFLON OR GRAPHITE

☒ IMPELLER CF-8M

☒ SHAFT Duplex

☒ BEARING CAST IRON GT25

☐ SHAFT SEAL VTS

☐ WEAR RING CF-8M

PERFORMANCE

PROPOSAL CURVE NO. (r/min)

☐ IMPELLER DIA RATED MAX. MIN. (mm)

☐ IMPELLER TYPE Closed

☐ RATED POWER (kw) EFFICIENCY (%)

☐ MINIMUM CONTINUOUS FLOW :

☐ THERMAL (m³/h) STABLE (m³/h)

☐ PREFERRED OPER. REGION TO (m³/h)

☐ ALLOWABLE OPER. REGION TO (m³/h)

☐ MAX. HEAD @ RATED IMPELLER (m)

☐ MAX. POWER @ RATED IMPELLER (kw)

☐ NPSHR AT RATED FLOW (m)

☒ MAX SUCTION SPECIFIC SPEED : 220 (rpm, m3/s, m)

☒ MAX . SOUND PRESS LEVEL REQ'D <85@1.0 m (dba)

UTILITY CONDITIONS

ELECTRICITY	VOLTAGE	PHASE	HERTZ
DRIVERS	400	3	50
HEATING			

SYSTEM VOLTAGE DIP ☒ 80% ☐ OTHER

STEAM	MAX. PRESS.	MAX. TEMP	MIN. PRESS.	MIN. TEMP
DRIVERS				
HEATING				

COOLING WATER: SOURCE

SUPPLY TEMP. (°C) MAX. RETURN TEMP. (°C)

NORM. PRESS. (bar) DESIGN PRESS. (bar)

MIN. RET. PRESS. (bar) MAX. ALLOW. D.P. (bar)

CHLORIDE CONCENTRATION : (mg/kg)

	CONSTRUCTION	SURFACE PREPARATION AND PAINT	Rev								
2	ROTATION : (VIEWED FROM COUPLING END) <input type="checkbox"/> CW <input type="checkbox"/> CCW	<input checked="" type="radio"/> MANUFACTURER'S STANDARD									
3	PUMP TYPE : (4.1)	SPECIFICATION NO. _____									
4	<input type="checkbox"/> VS1 <input type="checkbox"/> VS2 <input type="checkbox"/> VS3 <input checked="" type="checkbox"/> VS4 _____	PUMP : _____									
5	CASING MOUNTING :	<input checked="" type="radio"/> PRIMER _____									
6	<input type="checkbox"/> SUMP COVER PLATE <input type="checkbox"/> SEPARATE MOUNTII	<input checked="" type="radio"/> FINISH COAT _____									
7	<input type="checkbox"/> IN LINE <input type="checkbox"/> SEPARATE SOLE PLATE	BASEPLATE : _____									
8	CASING TYPE :	<input checked="" type="radio"/> PRIMER _____									
9	<input type="checkbox"/> SINGLE VOLUTE <input type="checkbox"/> MULTIPLE VOLUTE <input type="checkbox"/> DIFFUSER	<input checked="" type="radio"/> FINISH COAT _____									
10	CASE PRESSURE RATING :	<input checked="" type="radio"/> DETAILS OF LIFTING DEVICES _____									
11	<input type="radio"/> OH6 PUMP SUCTION REGION DESIGNED FOR MAWP (5.3.6)	SHIPMENT : _____									
12	<input checked="" type="checkbox"/> MAX. ALLOWABLE WORKING PRESSURE _____ (bar)	<input type="radio"/> DOMESTIC <input checked="" type="radio"/> EXPORT <input checked="" type="radio"/> EXPORT BOXING REQUIRED									
13	@ 40 (°C)	<input checked="" type="radio"/> OUTDOOR STORAGE MORE THAN 6 MONTHS									
14	<input type="checkbox"/> HYDRO TEST PRESSURE 1.5 X MAWP (bar)	REMARK: _____									
15	<input type="checkbox"/> NOZZLE CONNECTIONS :										
16	<table><tr><th>SIZE</th><th>FLANGE RATING</th><th>FACG</th><th>POSITION</th></tr><tr><td></td><td></td><td></td><td></td></tr></table>	SIZE	FLANGE RATING	FACG	POSITION						
SIZE	FLANGE RATING	FACG	POSITION								
17											
18	SUCTION										
19	DISCHARGE		#150 RF TOP								
20											
21	PRESSURE CASING AUX. CONNECTIONS :										
22	<table><tr><th>NO.</th><th>SIZE (DN)</th><th>TYPE</th></tr><tr><td></td><td></td><td></td></tr></table>	NO.	SIZE (DN)	TYPE							
NO.	SIZE (DN)	TYPE									
23	<input checked="" type="checkbox"/> DRAIN		VTS								
24	<input checked="" type="checkbox"/> VENT		VTS								
25	<input type="checkbox"/> WARM-UP										
26											
27	<input type="checkbox"/> MACHINED AND STUDDED CONNECTIONS :										
28	<input type="radio"/> CYLINDRICAL THREADS REQUIRED										
29	ROTOR :										
30	<input checked="" type="radio"/> COMPONENT BALANCE TO ISO 1940 G 1.0 (5.9.4.4)										
31	COUPLINGS :(6.2.2)										
32	<input type="radio"/> MANUFACTURER _____ <input checked="" type="checkbox"/> MODEL										
33	<input type="checkbox"/> RATING (kw per100 r/min) _____										
34	<input checked="" type="checkbox"/> SPACER LENGTH _____ (mm) <input checked="" type="checkbox"/> SERVICE FACT. MIN 1.5										
35	<input type="radio"/> COUPLING BALANCED TO ISO 1940-1 G 6.3										
36	<input type="radio"/> COUPLING WITH PROPRIETARY CLAMPING DEVICE										
37	<input type="radio"/> COUPLING PER ISO 14691										
38	<input type="radio"/> COUPLING PER ISO 14691										
39	<input type="radio"/> COUPLING PER API 671 <input type="radio"/> ASME B151										
40	<input checked="" type="radio"/> NON SPARK COUPLING GUARD (6.2.14C)										
41	<input type="radio"/> COUPLING GUARD STANDARD PER _____										
42	BASEPLATES:										
43	<input type="checkbox"/> API BASEPLATE NUMBER _____										
44	<input type="radio"/> NON-GROUT CONSTRUCTION (6.3.13)										
45	<input checked="" type="radio"/> OTHER Common baseplate for pump, driver and sealing system										
46	SEAL TYPE:										
47											
48	<input checked="" type="checkbox"/> SEAL MANUFACTURER _____										
49	<input checked="" type="radio"/> SEAL/AUXILIARY PLAN _____ 11/61 OR 14 /61										
50	REMARK: _____										
51	SEAL PLAN SHALL BE FINALIZED BY VENDOR.										
52											
53											
54											
		HEATING AND COOLING									
		<input type="radio"/> HEATING JACKET REQ D.									
		<input checked="" type="checkbox"/> COOLING REQ D.									
		<input type="checkbox"/> COOLING WATER PIPING PLAN _____									
		C.W. PIPING: _____									
		<input type="checkbox"/> PIPE <input type="checkbox"/> TUBING: _____ FITTINGS _____									
		C.W. PIPING MATERIALS: _____									
		<input type="checkbox"/> S.STEEL <input type="checkbox"/> C.STEEL <input type="checkbox"/> GALVANIZED									
		COOLING WATER REQUIREMENTS : _____									
		<input type="checkbox"/> BEARING HOUSING _____									
		HEAT EXCHANGER _____									
		TOTAL COOLING WATER _____									
		HEAT MEDIUM : <input type="radio"/> STEAM <input type="radio"/> OTHER									
		HEATING PIPING : <input type="radio"/> TUBING <input type="radio"/> PIPE									
		BEARING AND LUBRICATION									
		BEARING (TYPE / NUMBER) : _____									
		<input type="checkbox"/> RADIAL _____ /									
		<input type="checkbox"/> THRUF _____ /									
		LUBRICATION : _____									
		<input type="checkbox"/> GREASE <input checked="" type="checkbox"/> OIL									
		<input type="radio"/> PURGE OIL MIST <input type="radio"/> PURE OIL MIST									
		<input checked="" type="radio"/> CONSTANT LEVEL OILER PREFERENCE : _____									
		<input type="checkbox"/> OIL VISC. ISO GRADE _____									
		INSTRUMENTATION									
		<input type="radio"/> ACCELEROMETER _____									
		<input type="radio"/> PROVISION FOR MOUNTING ONLY									
		<input checked="" type="radio"/> FLAT SURFACE REQ D									
		<input type="radio"/> TEMP GAUGES									
		<input type="radio"/> PRESSURE GAUGE TYPE									
		REMARKS : _____									
		<input type="checkbox"/> MASSES									
		MASS OF PUMP (kg) _____									
		MASS OF BASEPLATE (kg) _____									
		MASS OF DRIVER (kg) _____									
		TOTAL MASS (kg) _____									

SPARE PARTS (TABLE 18)

VERTICAL PUMPS (CONT.)

Rev

2 ☒ START-UP ☐ NORMAL MAINTENANCE

3 ☒ SPECIFY **2 YEARS OPERATION**

4

5 **OTHER PURCHASER REQUIREMENTS**

6 ☒ COORDINATION MEETING REQUIRED

7 ☒ MAXIMUM DISCHARGE PRESSURE TO INCLUDE

8 ☒ MAX RELATIVE DENSITY

9 ☒ MAX DIA. IMPELLERS AND / OR NO. OF STAGES

10 ☐ OPERATION TO TRIP SPEED

11 ☐ CONNECTION DESIGN APPROVAL

12 ☐ TORSIONAL ANALYSIS REQUIRED

13 ☐ TORSIONAL ANALYSIS REPORT

14 ☒ PROGRESS REPORTS

15 ☐ OUTLINE OF PROCEDURES FOR OPTIONAL TESTS

16 ☐ ADDITIONAL DATA REQUIRING 20 YEARS RETENTION

17 MANIFOLD PIPING TO SINGLE CONNECTION

18 ☒ VENT ☐ VENT ☐ COOLING WATER

19 ☐ MOUNT SEAL RESERVOIR OFF BASEPLATE

20 ☒ FLANGES REQ D IN PLACE OF SOCKET WELD UNIONS

VERTICAL PUMPS

24 ☒ **VERTICAL PUMPS**

25 ☐ PUMP THRUST : (+)UP _____ (-)DOWN _____

26 AT MIN. FLOW _____ (N) _____ (N)

27 AT RATED FLOW _____ (N) _____ (N)

28 MAX THRUST _____ (N) _____ (N)

29 ☐ SOLE PLATE REQ D. _____ (m) X _____ (m)

30 ☐ SEPARATE MOUNTING PLATE REQUIRED

31 ☐ SOLE PLATE THICKNESS _____ (mm)

32 COLUMN PIPE : ☒ FLANGED ☐ THREADED

33 ☐ DIAMETER _____ (mm) LENGTH _____ (m)

34 GUIDE BUSHINGS ☐ ☐

35 ☐ NUMBER _____

36 ☐ LINE SHAFT BEARING SPACING _____ (mm)

37 GUIDE BUSHINGS LUBE :

38 ☐ WATER ☐ OIL

39 ☐ GREASE ☐ PUMPAGE

40 LINESHAFT : ☒ OPEN ☐ ENCLOSED

41 ☐ LINE SHAFT DIAMETER : _____ (mm)

42 ☐ TUBE DIAMETER : _____ (mm)

43 LINESHAFT COUPLING :

44 ☐ LINE SHAFT DIAMETER : ☐ SLEEVE & KEY ☐ THREADED

45 ☐ SUCTION CAN THICKNESS _____ (mm)

46 ☐ LENGTH _____ (m)

47 ☐ DIAMETER _____ (m)

48 ☐ SUCTION STRAINER TYPE _____

49 ☐ FLOAT & ROD ☐ FLOAT SWITCH

☐ PUMP AND STRUCTURE DYNAMIC ANALYSIS

☐ DRAIN PIPED TO SURFACE

QA INSPECTION AND TESTING

☒ SHOP INSPECTION ☒ PERF. CURVE APPROVAL

☐ TEST WITH SUBSTITUTE SEAL

TEST	NON-WIT	WIT	OBSERVE
<input checked="" type="radio"/> HYDROSTATIC TEST OF BOWLS AND COLUMN	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/> HYDROSTATIC	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input checked="" type="radio"/> PERFORMANCE	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input type="radio"/> RETEST ON SEAL LKGE	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> NPSH	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> COMPLETE UNIT TEST	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> SOUND LEVEL TEST	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> CLEANLINESS PRIOR TO FINAL ASSEMBLY	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> MECHANICAL RUN UNTIL OIL TEMP STABLE	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> 4 HR. MECH. RUN TEST	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
<input type="radio"/> TRUE PEAK VELOCITY DATA	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> RESONANCE TEST	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> AUXILIARY EQUIPMENT TEST (7.3.4.5)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="checkbox"/> IMPACT TESTING	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/> PER EN 13445			
<input type="radio"/> PER ASME VIII			
<input checked="" type="radio"/> VENDOR KEEP REPAIR AND HT RECORDS			
<input checked="" type="radio"/> VENDOR SUBMIT TEST PROCEDURES			
<input checked="" type="radio"/> VENDOR SUBMIT TEST DATA WITHIN 24 HOURS			
<input type="radio"/> INCLUDE PLOTTED VIBRATION SPECTRA			
<input checked="" type="radio"/> RECORD FINAL ASSEMBLY RUNNING CLEARANCES			
<input checked="" type="radio"/> COMPLETION OF INSPECTION CHECK LIST			
<input checked="" type="radio"/> MATERIAL CERTIFICATION REQUIRED			
<input checked="" type="radio"/> CASING <input checked="" type="radio"/> IMPELLER <input checked="" type="radio"/> SHAFT			
<input checked="" type="radio"/> OTHER WEAR RING _____			
<input checked="" type="radio"/> CASTING REPAIR PROCEDURE APPROVAL REQ D			
<input checked="" type="checkbox"/> INSPECTION REQUIRED FOR CONNECTION			
WELDS			
<input checked="" type="checkbox"/> MAG PARTICLE <input checked="" type="checkbox"/> LIQUID PENETRANT			
<input type="checkbox"/> RADIOGRAPHIC <input type="checkbox"/> ULTRASONIC			
<input checked="" type="checkbox"/> INSPECTION REQUIRED FOR CASTINGS			
<input checked="" type="checkbox"/> MAG PARTICLE <input checked="" type="checkbox"/> LIQUID PENETRANT			
<input type="checkbox"/> RADIOGRAPHIC <input type="checkbox"/> ULTRASONIC			
<input type="radio"/> HARDNESS TEST REQUIRED			


KEY

SUMP ARRANGEMENT

- 1 GRADE
- 2 LOW LIQUID LEVEL
- 3 CENTERLINE OF DISCHARGE
- l_1 SUMP DEPTH
- l_2 PUMP LENGTH
- l_3 CENTERLINE DISCHARGE HEIGHT
- l_4 HEIGHT OF GRADE ABOVE LOW LIQUID LEVEL
- l_5 DATUM ELEVATION, FIRST-STAGE IMPELLER
- l_6 SUBMERGENCE REQUIRED
- $\varnothing d$ SUMP DIAMETER

REFER TO HYDRAULIC INSTITUTE STANDARDS FOR DEFINITIONS

- | | |
|--|--|
| <input checked="" type="radio"/> l_1 _____ (m) | <input type="checkbox"/> l_2 _____ (m) |
| <input checked="" type="radio"/> $\varnothing d$ _____ (m) | <input type="checkbox"/> l_6 _____ (m) |
| <input checked="" type="radio"/> l_4 _____ (m) | <input type="checkbox"/> l_3 _____ (m) |
| | <input type="checkbox"/> l_5 _____ (m) |



	REMARKS	Rev.
1	1) VTS: Vendor to Advise	
2	2) Material to be confirmed by Vendor.	
3	3) Electrical motor thermal protection shall be provided by vendor.	
4	4) Electric Motor shall be supplied according to low voltage induction motors DOC.NO: 7111-BD-40-EL-SP-0012.	
5	5) Refer to site condition: 7111-BD-40-PR-RR-0003.	
6	6) Special Tools Shall Be Supplied by Vendor (if required)	
7	7) Vendor Shall Consider and Supply All Necessary Instruments for Safe Operation and Start-up.	
8	8) Mechanical Seal Data Sheet Shall Fill In by Vendor as per API 682	
9	9) Allowable Loads on Flanges Shall be at Least TWO TIMES of API 610.	
10	10) Purchaser/Company Shall Have the Right to Dismantle the Pumps After Mechanical Running Test, If the Test Do	
11	Not Meet API 610 Requirements.	
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		