

GLOBE VALVE

Sr#	Description	Qty
1	<u>GLOBE VALVE:</u> Brass. Application: HVAC System Media : Clean Water Nominal pressure:PN16 Wheel Type: Non Rising Stem End connection: Screwed in bonnet. Material of Construction: Brass Temperature Range : 5 to 80 ⁰ C Hydrostatic test pressure, Pressure/Temperature Rating Material Specification: To be specified by the manufacturer. Size: 2"	07
2	<u>GLOBE VALVE:</u> Brass. Application: HVAC System Media : Clean Water Nominal pressure:PN16 Wheel Type: Non Rising Stem End connection: Screwed in bonnet. Material of Construction: Brass Temperature Range : 5 to 80 ⁰ C Hydrostatic test pressure, Pressure/Temperature Rating Material Specification: To be specified by the manufacturer. Size: 1"	10
3	<u>GLOBE VALVE:</u> Brass. Application: HVAC System Media : Clean Water Nominal pressure:PN16 Wheel Type: Non Rising Stem End connection: Screwed in bonnet. Material of Construction: Brass Temperature Range : 5 to 80 ⁰ C Hydrostatic test pressure, Pressure/Temperature Rating Material Specification: To be specified by the manufacturer. Size: 1/2"	40
<u>Notes:</u> <ol style="list-style-type: none"> Make: Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran Valves, CEPEX, KSB Germany. Origin: EU/USA/Japan 		