


30T Vertical Lead acid battery bushing/terminal Die Casting Machine (Semi auto)

图片 Photo	名称 Name	基本参数 Parameters	名称 Name	基本参数 Parameters
	合模力 Locking Force	300KN	电动机功率 Motor Power	5.5KW
	拉杠间距 Tie Bars Inner Space	345 × 295mm	蓄能器容量 Accumulator Capacity	16L
	动模行程 Moving Clamping Plate	125mm	系统工作压力 Vane Pump Working Pressure	7.0Mpa
	铸型高度范围 Profiling Thickness	110 – 190mm	电热管功率 Electric Heating Tube Power	9.5KW
	压射力 Injection Pressure	30KN	保温套 Heater Hand Power	1KW
	铸射行程 Injection Stroke	120mm	油箱容量 Oil Tank Capacity	170L
	有效射出量（铅） Dosage of Fluid Metal Pershot（Pb）	1000g	机器重量 Machine Weight	~2500Kg
	坩埚容量(铅) Crucible Effective Capacity（Pb）	300Kg	设备尺寸 Machine Dimensions	170 × 90 × 250cm*2Parts
	油泵流量 Vane Pump	30L/min		
Remark: All parameters&photo are reference only, Reserve the right to change the parameters without prior notice.				