

# Thermal Imaging IR Camera

Page # 2

Sr. No.		Qty.																																		
1.	<div>Thermal Imaging IR Camera</div> <div><div>Specifications</div><table><tr><td>IR resolution</td><td>1024 x 768</td></tr><tr><td>Object temperature range</td><td>-40°C to 2000°C</td></tr><tr><td>Digital zoom</td><td>8x</td></tr><tr><td>Lenses</td><td>Should include 45°x34° (21 mm), 28° x 21° (36 mm), 12° x 9° (83 mm), 7° x 5.3° (142 mm), 3x zoom lenses. Prices of optional lenses should be quoted separately.</td></tr><tr><td>Image frequency</td><td>30 Hz</td></tr><tr><td>Spectral range</td><td>7.5 - 14.0 μm</td></tr><tr><td>Thermal Sensitivity</td><td>20 mK</td></tr><tr><td>Display</td><td>4.3", 800 x 480 px</td></tr><tr><td>Viewfinder</td><td>Built-in, 800 x 480 px</td></tr><tr><td>Digital Camera</td><td>5 MP</td></tr><tr><td>Accuracy</td><td>±1°C</td></tr><tr><td>Position</td><td>Automatic distance detection</td></tr><tr><td>Alarm</td><td>Above, below, interval, moisture, insulation, measurement alarms</td></tr><tr><td>Focus</td><td>Autofocus and manual</td></tr><tr><td>Image Modes</td><td>Infrared, visual, Picture-in-Picture mode</td></tr><tr><td>Power Supply</td><td>220 VAC, Single Phase, 50 Hz</td></tr><tr><td colspan="2"><div><div><div>○ Should include PC Software, rechargeable battery along with charger, transport case, SD card, tripod, neck strap, all required video cables, lenses mentioned above, calibration certificate, calibration kit and operation manual in English language.</div><div>○ Pre-shipment inspection and training of one person for one week at manufacturer's site.</div><div>○ Installation and testing at client's site.</div></div></div></td></tr></table></div>	IR resolution	1024 x 768	Object temperature range	-40°C to 2000°C	Digital zoom	8x	Lenses	Should include 45°x34° (21 mm), 28° x 21° (36 mm), 12° x 9° (83 mm), 7° x 5.3° (142 mm), 3x zoom lenses. Prices of optional lenses should be quoted separately.	Image frequency	30 Hz	Spectral range	7.5 - 14.0 μm	Thermal Sensitivity	20 mK	Display	4.3", 800 x 480 px	Viewfinder	Built-in, 800 x 480 px	Digital Camera	5 MP	Accuracy	±1°C	Position	Automatic distance detection	Alarm	Above, below, interval, moisture, insulation, measurement alarms	Focus	Autofocus and manual	Image Modes	Infrared, visual, Picture-in-Picture mode	Power Supply	220 VAC, Single Phase, 50 Hz	<div><div><div>○ Should include PC Software, rechargeable battery along with charger, transport case, SD card, tripod, neck strap, all required video cables, lenses mentioned above, calibration certificate, calibration kit and operation manual in English language.</div><div>○ Pre-shipment inspection and training of one person for one week at manufacturer's site.</div><div>○ Installation and testing at client's site.</div></div></div>		01
IR resolution	1024 x 768																																			
Object temperature range	-40°C to 2000°C																																			
Digital zoom	8x																																			
Lenses	Should include 45°x34° (21 mm), 28° x 21° (36 mm), 12° x 9° (83 mm), 7° x 5.3° (142 mm), 3x zoom lenses. Prices of optional lenses should be quoted separately.																																			
Image frequency	30 Hz																																			
Spectral range	7.5 - 14.0 μm																																			
Thermal Sensitivity	20 mK																																			
Display	4.3", 800 x 480 px																																			
Viewfinder	Built-in, 800 x 480 px																																			
Digital Camera	5 MP																																			
Accuracy	±1°C																																			
Position	Automatic distance detection																																			
Alarm	Above, below, interval, moisture, insulation, measurement alarms																																			
Focus	Autofocus and manual																																			
Image Modes	Infrared, visual, Picture-in-Picture mode																																			
Power Supply	220 VAC, Single Phase, 50 Hz																																			
<div><div><div>○ Should include PC Software, rechargeable battery along with charger, transport case, SD card, tripod, neck strap, all required video cables, lenses mentioned above, calibration certificate, calibration kit and operation manual in English language.</div><div>○ Pre-shipment inspection and training of one person for one week at manufacturer's site.</div><div>○ Installation and testing at client's site.</div></div></div>																																				
<div>Warranty: One year</div> <div>Brand: FLIR T1020 or equivalent</div> <div>Origin: USA/W. Europe/Japan</div>																																				

Check List

Page # 3

Thermal Imaging IR Camera

Sr. No.	Description	Yes	No	N.A.
1	Make, model no. and origin is mentioned			
2	Calibration certificate and calibration kit is provided			
3	Resolution and temperature range are mentioned			
4	Optional lenses are provided and quoted separately			
5	Optical zoom lenses are provided			
6	All required accessories are provided			
7	Optional Item prices are quoted separately			
8	Warranty period is clearly mentioned			
9	Power supply is 220V, 50Hz, Single Phase			

Note: N.A = Not Applicable