

SELF CONTAINED BREATHING APPARATUS AND SELECTABLE GALLONAGE

| Sr# | Description | Qty |
|--|--|-----|
| 1. | <p><u>SELF-CONTAINED BREATHING APPARATUS:</u></p> <ul style="list-style-type: none"> • Complete SCBA set with cylinder, face-piece, HP/LP hoses and back plate. • Either 6-Liter cylinder w/300 Bar WP or 9-Liter cylinder w/200 Bar WP. • Lightweight Carbon/Alloy (Composite) cylinder • Two stage regulator for cylinder pressure reduction and single stage mask mounted regulator (LDV) port. • Comfortable Back-plate assembly, with nylon/Kevlar shoulder and lumbar straps/pads. • Full-face mask with quick disconnect coupling. Medium size. • Low pressure alarm/whistle at 50-bar • Service time~45minutes • Hard case for storage and carrying of equipment • Cylinder and LDV connections must compatible either with MSA AUER, BD-95 or DPI-Sekur, Diablo (EN144M18x5) | 08 |
| 2. | <p><u>MID-RANGE SELECTABLE GALLONAGE HAND CONTROL NOZZLE:</u></p> <ul style="list-style-type: none"> • EN 15182-2 Type-3 compliant, • 2.5" (65mm) tip size British Instantaneous Male coupling, • Lightweight hard-coated anodized Aluminum construction, • Combination pattern Nozzle w/ multiple flow- settings (300-950 LPM @ 6 bar with 5 flow settings), • Straight stream to fog in quarter turn, • SS filter mesh and spinning teeth | 24 |
| <p><u>NOTES:</u></p> <p>a. Make: EU/USA Origin/Manufacturer</p> | | |