

CHECK VALVE

Sr#	Description	Qty
1	<u>CHECK VALVE:</u> Application: HVAC System Media : Clean Water Nominal pressure:PN16 Type: Swing Check Valve Bolted Cover End connection: Flanged connection/flanged to DIN-2633 or Equivalent. Flange type: Raised face Material of Construction: Cast Iron, Bronze Trim, S.S pin Hydrostatic test pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range : 5 to 80°C Size: 5"Ø	02
2	<u>CHECK VALVE:</u> Application: HVAC System Media : Clean Water Nominal pressure:PN16 Type: Swing Check Valve Bolted Cover End connection: Flanged connection/flanged to DIN-2633 or Equivalent. Flange type: Raised face Material of Construction: Cast Iron, Bronze Trim, S.S pin Hydrostatic test pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range : 5 to 80°C Size: 4"Ø	02
3	<u>CHECK VALVE:</u> Application: HVAC System Media : Clean Water Nominal pressure:PN16 Type: Swing Check Valve Bolted Cover End connection: Flanged connection/flanged to DIN-2633 or Equivalent. Flange type: Raised face Material of Construction: Cast Iron, Bronze Trim, S.S pin Hydrostatic test pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range : 5 to 80°C Size: 2-1/2"Ø	02
4	<u>CHECK VALVE:</u> Application: HVAC System Media : Clean Water Nominal pressure:PN16 Type: Swing Check Valve Bolted Cover End connection: Flanged connection/flanged to DIN-2633 or Equivalent.	02

CHECK VALVE

	Flange type: Raised face Material of Construction: Cast Iron, Bronze Trim, S.S pin Hydrostatic test pressure, Pressure/Temperature Rating: To be specified by the manufacturer. Temperature Range : 5 to 80 ⁰ C Size: 2"Ø	
Notes: <ul style="list-style-type: none">a. Make: Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran Valves, CEPEX, KSB Germany.b. Origin: EU/USA/Japan		