

WELDING HELMETS AND WELDING HANDSHIELDS

Multi Vision flip-up with safety helmet connector



Welding safety helmet combinations. Optionally a leather welding spatter protector is available that prevents spatters from falling between the welding helmet and the safety helmet.

Safety helmet not included.

EN 175 S

Product nr	Description	Packing
44.46.60580	Multi Vision with flip-up insert and Speedy 5000 quick lock, 51 x 108 mm.	1/10


Quick fastener for welding helmet safety helmet combination



The spare parts of the quick connect system offer the option to change a standard welding helmet into a welding helmet that can be fitted on a safety helmet.

Product nr	Description	Packing
44.46.63517	Speedy quick lock for Multi Vision.	1/10

44



HEAD PROTECTION

Uvex Airwing B-S-WR safety caps



All the models in the Uvex Airwing safety helmet series are equipped with a 6-point textile strip carrier basket. Rotating size adjusters are available as an optional extra to enable easy size alteration for comfort during use. These safety helmets meet the additional very low temperature requirement, covering conditions down to -30°C.

Benefits overview

- Lightweight helmet with attractive design.
- Perfect fit, high wearing comfort.
- Helmet shell made of polyethylene.
- Side slots for attaching ear defenders and/or visors.
- 6-point textile suspension harness.
- Airwing B - 3 variable air vents.

EN 397.

Product nr	Description	Packing
36.41.28763-200	Yellow.	1/25
36.41.28763-300	Blue.	1/25
36.41.28763-400	White.	1/25
36.41.28763-600	Green.	1/25

Uvex Airwing spare parts

Product nr	Description	Packing
36.41.28836	Headgear	1/1
36.41.31413	Sweatband.	1/1

Speedy quickmount



Speedy quick lock for quick and firm mounting of a welding helmet to a safety cap. The welding helmet can easily be lifted of the safety cap by pushing the clips out.

Product nr	Description	Packing
44.46.63517	Speedy quickmount.	1/1

Bilsom Clarity C1H ear protectors



BILSOM Clarity C1H, light blue.

Grey-blue ear protectors that still allow you to hear speech. Can be attached in the slot on the safety helmet using 3 different types of adapters (supplied).

H=26dB M=23dB L=19dB SNR=26dB
 H= high tonal range; M=medium tonal range;
 L=low tonal range; SNR=Single Number Rating

EN 352-1

Product nr	Description	Packing
42.31.29484	Clarity C1H Earmuffs, per pair.	1/10

