

## HEATING TAPES

Sr#	Description	Qty.
01	<b><u>TUBULAR HEATERS:</u></b> <ul style="list-style-type: none"> <li>Mineral Insulated Heating Cable</li> <li>Sheath Material: SS-316/SS-304</li> <li>Heating Element: Nickel-Chrome alloy</li> <li>Electrical Insulation : Magnesium Oxide</li> <li>Max. Temperature : 500°C</li> <li>Connector: Water Proof</li> <li>Cold End : 0.5 meter on both sides</li> <li>Length : 35 meter or nearest</li> <li>Power: 9.5-10.0 KW (220V, 50 Hz)</li> </ul>	12
02	<b><u>TUBULAR HEATERS:</u></b> <ul style="list-style-type: none"> <li>Mineral Insulated Heating Cable with Inconel-600 metal sheath.</li> <li>Electrical Load: 9-10 KW, 220V, 50 Hz.</li> <li>Length: 30-35 meter</li> <li>Heating Element: Nickel-Chrome alloy</li> <li>Element Resistance : 0.15 ohm/meter or nearest</li> <li>Electrical Insulation: Magnesium Oxide or material with equivalent properties.</li> <li>Max. Temperature : 1000°C or nearest</li> <li>Heater Outer Dia.: 6.5mm or nearest</li> <li>Connectors : Water Proof</li> <li>Cold Ends: 2 X 500 mm</li> <li>Thread Glands: PG 11</li> </ul>	08
<b>Notes:</b> <ol style="list-style-type: none"> <li><b>Make :</b> ISOHEAT or Equivalent or Chinese brand of same quality and reput</li> <li><b>Note:</b> Provide Technical Literature along with quotation in English.</li> </ol>		