

Sr.#	Items's Description	Unit	Qty.
1	Submersible Feed Pump with flow rate of 120 m ³ /hr and head 10~12m, construction material body, impeller in cast iron and shaft in stainless steel, equipped with electric motor of rated power as per manufacturer, 400 volts, 50 Hz, 3 phase and IP68, complete with all aspects.	No.	2
2	Feed submersible pump with a rated flow rate of 40 m ³ /hr and rated head of 10m, casing design pressure as per manufacturer, casing, impeller in cast iron construction and shaft in SS construction with electric motor power rated as per manufacturer, 400 volts, 50 Hz and 3~, equipped with lifting arrangements, complete with all fitting and arrangements.	No.	2
3	Feed submersible pump with a rated flow rate of 40 m ³ /hr and rated head of 10m, casing design pressure as per manufacturer, casing, impeller in cast iron construction and shaft in SS construction with electric motor power rated as per manufacturer, 400 volts, 50 Hz and 3~, equipped with lifting arrangements, complete with all fitting and arrangements.	No.	2
4	Horizontal centrifugal Feed pump for Sand filter with flow rate of 40 m ³ /hr and head 20~30m, body and impeller construction in SS304 and shaft in stainless steel, equipped with electric motor of rated power as per manufacturer, 400 volts, 50 Hz, 3 phase and IP55, complete with all aspects.	No.	2
5	Centrifugal pump with a rated flow rate of 65 m ³ /hr and rated head of 20m, casing design pressure as per manufacturer, casing, impeller in cast iron construction and shaft in SS construction with electric motor have rated power as per manufacturer, 400 volts, 50 Hz and 3~, complete with all fitting and arrangements.	No.	2
6	Sludge positive displacement feed pump with rated flow rate of 8m ³ /hr and 10m rated head, casing pressure as per manufacturer, casing in cast iron and shaft in SS constructed with original manufacturer electric motor with rated power as per manufacturer, 400V, 50 Hz, IP55 and 3 phase. Pump shall equipped with all fittings and complete accessories.	No.	2
7	Polymer feed gear pump rated at 0.37 kw, 400 V, 50 Hz, 3 phase, complete with all fittings and accessories.	No.	2
8	Submersible Pump with flow rate of 55 m ³ /hr and head of 10~15m, construction material casing body and impeller in cast iron, shaft stainless steel, with electric motor of rated 400volts, 50 Hz, 3 phase and IP68, complete with all aspects.	No.	2