

## HIGH PRESSURE TEMP. NEEDLE VALVES

Sr#	Description	Qty
1	<p><b><u>SOCKET WELDED NEEDLE VALVES</u></b></p> <p><b>Specifications:</b></p> <p>Size: ½"</p> <p>Maximum Pressure; 45 MPa,</p> <p>Maximum tolerant Temperature: 649 °C</p> <p>Medium: Steam</p> <p>Material: SS3 16</p> <p>Model: SS-6NBSW8T-G</p>	40
2	<p><b><u>4-WAY PRESSURE GAUGE NEEDLE VALVES</u></b></p> <p><b>Specifications:</b></p> <p>First way is 20x 1.5 NPTM mm for Input steam</p> <p>Second way is 20x1.5 NPTF for Gauge side</p> <p>Third way is used by an installed needle valve for isolation</p> <p>Fourth way is used by an installed needle valve for purging</p> <p>Maximum Working Pressure; 32 MPa</p> <p>Maximum Working Temperature: 550 °C</p> <p>Medium: Steam</p> <p>Material: SS316</p> <p>Model: J19H-320/Equivalent</p>	20
<p><b><u>Notes:</u></b></p> <p style="padding-left: 20px;">a. Make: Swagelok/ Equivalent</p>		