

Sr#	Description	Qty
1	<p data-bbox="151 55 813 83"><u>FLATBED GLASS GRINDING MACHINE:</u></p> <p data-bbox="151 91 407 125">Specifications:</p> <p data-bbox="151 132 925 166">Grinding Disc Size: 12" (30 cm)</p> <p data-bbox="151 174 904 208">Motor with variable speed control: 0-380 RPM</p> <p data-bbox="151 215 1184 298">Lock load flexible water feed system with drain Ultra Strong polypropylene tray with anti-spray brush top</p> <p data-bbox="151 305 477 339">Cast iron wheel head</p> <p data-bbox="151 347 638 381">Bearing water protection shield</p> <p data-bbox="151 388 659 422">Heavy duty stainless steel frame</p> <p data-bbox="151 429 596 464">Self-aligning sealed bearings</p> <p data-bbox="151 471 988 505">Voltage: 220 Volts, 60 Hz</p> <p data-bbox="151 512 841 547">Additional Grinding discs: 02 No.</p>	One
2	<p data-bbox="151 566 708 594"><u>GLASS CUTTING SAW MACHINE:</u></p> <p data-bbox="151 601 666 636">(for Glass, Quartz arid Ceramics)</p> <p data-bbox="151 643 407 677">Specifications:</p> <p data-bbox="151 684 862 718">Cutting Wheel Diameter: 250 mm</p> <p data-bbox="151 726 862 760">Flange Diameter: 100 mm</p> <p data-bbox="151 767 841 801">Maximum free cutting depth: 65 mm</p> <p data-bbox="151 809 1030 843">Cutting Table Plate size: 350 mm x 320 mm</p> <p data-bbox="151 850 869 884">Table travel range: 170 mm</p> <p data-bbox="151 891 638 926">Heavy duty stainless steel base</p> <p data-bbox="151 933 1002 967">Water pump with stainless steel clearing vessel in base</p> <p data-bbox="151 974 988 1009">Voltage: 220 volts, 60 Hz</p> <p data-bbox="151 1016 834 1036">Additional Cutting discs: 10 No.</p>	One