



5. ASME Y14.5-2009 COMPLIANT 服从asme Y14.5-2009

MATERIAL: 416 STAINLESS STEEL
ALTERNATE MATERIAL: 304 STAINLESS STEEL

REV. 1: 2.803 WAS 2.743, 2.298 WAS .238, 2.200 WAS .150	REV. 2: (2) KNURLS WERE (1) (1.331 START OF KNURL)	REV. 3: (1) LONG KNURL WAS (2) .468 LG KNURLS	REV. 4, ECO-7161: 2.255/.245 FLAT WAS 2.280/.270, 4-40 WAS 2.18-32, .300 LG WAS .200	REVISIONS			TOLERANCES		PURCHASED SHAFT					
				NO.	DATE	BY	UNLESS OTHERWISE SPECIFIED							
				1	6-3-15	ACR	.XX = $\pm .01$ [± 0.25]		DRAWN BY	ACR	SCALE	1=1	MAT'L	SEE NOTE
				2	6-8-15	ACR	.XXX = $\pm .005$ [± 0.13]		CHK'D		DATE	4-27-15	DRAWING NO.	208677
				3	6-25-15	ACR	ANG. = $\pm 1^\circ$		ORIGINAL DWG.	208025	REV	10	APP'D	
4	12-15-15	ACR												
5														