

S. No	Description/Specifications/Part No. of Scientific/Technical/ Administrative Stores	Qty Required (Nos)
1	2	4
1.	<p>Thermocouples</p> <p>K-Type thermocouple (SS Sheathed, Fitted with PVC male/Female connectors through compensation cable as in picture attached,)</p> <ul style="list-style-type: none"> i. Diameter= 1.8-2.0 mm , SS sheathed Length = 1 meter Compensation cable length before PVC male/female connector = 1 meter ii. Diameter= 3.0 mm , SS sheathed Length = 1 meter Compensation cable length before PVC male/female connector = 1 meter <p>R-Type thermocouple (SS Sheathed, Fitted with PVC male/Female connectors through compensation cable as in picture attached,)</p> <ul style="list-style-type: none"> i. Diameter= 3.0 mm SS sheathed Length = 1 meter Compensation cable length before PVC male/female connector = 1 meter ii. Diameter= 5.0 mm , SS sheathed Length = 1 meter, 1.5 meter Compensation cable length before PVC male/female connector = 1 meter <p>Note: i. Literature and Pictures of thermocouples must be provided by Supplier in quotation/offer for evaluation. ii. Calibration certificate must be proved with supplied items</p>	<p>100</p> <p>50</p> <p>100</p> <p>50 each</p>

