

| Sr. No. | Description | Qty | | | | | | | | | | |
|---|--|------------------|---------------------|------------------------|----------------|---------------|-------------------|-----------------------|---------------|--------------|----------------------------|----|
| 1. | <div>Salt Spray Tester</div> <div>Specifications</div> <table><tr><td>Test Temperature</td><td>35°C±1°C / 50°C±1°C</td></tr><tr><td>Inside Dimensions (cm)</td><td>160 x 100 x 50</td></tr><tr><td>Tank Capacity</td><td>25l Salt Solution</td></tr><tr><td>Test Specimen 15°/30°</td><td>136PCS/136PCS</td></tr><tr><td>Power Supply</td><td>220 V, Single Phase, 50 Hz</td></tr></table> <div><ul style="list-style-type: none">Should have a control panel for all function settings, overheating protection device, water warning device, digital temperature control ±1°C, warning alarm and mist spray should be distributed evenly.Pre-shipment inspection and training of one person for one week at manufacturer's site.Installation and testing at client's site.Calibration CertificateAll necessities attachment required for operation of instrument.Manual in english</div> | Test Temperature | 35°C±1°C / 50°C±1°C | Inside Dimensions (cm) | 160 x 100 x 50 | Tank Capacity | 25l Salt Solution | Test Specimen 15°/30° | 136PCS/136PCS | Power Supply | 220 V, Single Phase, 50 Hz | 01 |
| Test Temperature | 35°C±1°C / 50°C±1°C | | | | | | | | | | | |
| Inside Dimensions (cm) | 160 x 100 x 50 | | | | | | | | | | | |
| Tank Capacity | 25l Salt Solution | | | | | | | | | | | |
| Test Specimen 15°/30° | 136PCS/136PCS | | | | | | | | | | | |
| Power Supply | 220 V, Single Phase, 50 Hz | | | | | | | | | | | |
| <div>Warranty: One year</div> <div>Origin: USA/Europe/Japan/China OR Equivalent</div> | | | | | | | | | | | | |