

## **AUTOMATIC & MANUAL COIL WINDING MACHINE**

<b><u>TECHNICAL SPECIFICATIONS</u></b> <b>AUTOMATIC &amp; MANUAL COIL WINDING MACHINE</b>
<b><u>AEX-02 DOUBLE SPINDLE SIDE LOADING MACHINE: (Qty 01)</u></b> <b><u>Production Capability:</u></b> Wire dia (mm): 0.02-0.08, Winding Width (mm): 70, Bobbin dia (mm): 60, Speed(max): 8000RPM and other built in salient and technical features of AEX-02 model of ACME Mechatronics Inc. or Equivalent
<b><u>AEX-01 SINGLE SPINDLE SIDE LOADING MACHINE: (Qty 01 )</u></b> <b><u>Production Capability:</u></b> Wire dia (mm): 0.02-1.0, Winding Width (mm): 100, Bobbin dia (mm): 80, Speed(max): 9000RPM and other built in salient and technical features of AEX-01 model of ACME Mechatronics Inc. or Equivalent
<b><u>NZ-02 MANUAL COIL WINDING MACHINE: (Qty 02)</u></b> Model: NZ-2, Applicable Gauge: AWG19#-37#(SWG20#-40#), Applicable Diameter of Wires: 0.0047 - 0.0358"(0.12 - 0.91 mm), Diameter of Coils Fit to be Wound: 0.4724 - 5.9055" (12 - 150 mm), Length of Coils Fit to be Wound: 0.2362 - 4.3307" (6a - 110 mm), Counting Range: 0 - 2500 Rounds, Transmission Ratio: 1:6 (Fast), I:1.5 (Slow), Length of Coils Applying to the Wire-Discharging Stand: 3.3465" (85mm), Diameter of Coils Applying to the Wire-Discharging Stand: 5.1181"(130mm), or Equivalent
<b><u>Notes:</u></b> a. Item must include standard and optional accessories with catalogues/manuals.