	1	-	- T	MOTOR NAME OF STREET	SPECIFICALI	ONS OF BRAND NEW HOLEN THE BOLLDOLLIN
12.			Sr. No.	Res	FNC: 21/KJA-13:	
	1	. 1	1	-	TYPE	All hydraulic heavy duty large size track type
			.		8 1 14	Type: semi universal (S-U)
		[				ii. Width: 4000 mm
1		1		i	i	ii. Height: 1750 mm
1				· —-	i	v. Lift height: 1500 - 1600 mm
		7	,	ı	RIADE	v. Drop below ground: 500 - 600 mm
		MAKE	2			vi. Pitch: 225 - 250 mm
		RE			· ·	vii. It should be attached with machine body using two hydraulic tilt cylinders and
	-					angled stabilizing braces.
7	4 5	5	i '			viii. It should be equipped with replaceable cutting plates at edges for better
1	CHALMEN FIAT ALL	CATERPILLA				cutting of sandstone.
'	7 .	4				Capable for pushing, digging, excavating, leveling, crowing, stumping,
17	MERS,	2	3		CAPACITY	ditching, in hilly areas.
7	20	0		١.		ii. Capable for dozing of 12m³ volume of soil.
1	52	7		1		iii. Capable for working at slopes up to 30°.
1	2 20	A				i. It should be crawler / track type.
	6	$\sim$	4	1	UNDERCARRIAGE	ii. It should be heavy duty and its components be enhanced such as steel plating for incredible strength to make bulldozer capable for usage in rough terrain
(	75					and rocky environment.
1	JOHN D	天	-	+		i. Type: Shank ripper
ALC: N	T T	Ö				ii. Number of rippers: 03 No.
Cold School	10	3				iii. Ripping depth: 800 - 900 mm
	50	KOMATS	5		RIPPERS	iv. Lifting height: 800 - 900 mm
	900	5			e e	iv. End points of rippers should be capable for cutting the sandstone and be
	ML	ž				easily replaceable.
,	36			1	GR. THOU MAD CHARLES CONTINUED ON EXPLORATION IN COMPANY OF MICH. ACCUSED AND	All components of buildozer should be driven through suitable CUMMINS,
	RE,	CASE,	6		ENGINE	CATERPILLER or IVECO make water cooled diesel engine. Specifications
ı	7.	35	-	+		may be mentioned in the bid.  i. Should be suitable to work in dust and typical desert conditions with ambient
TOTAL STATE	10NG	201				temperature ranging from -5 to + 55°C.
State (Ave.	22	00	7	1	HYDRUALIC SYSTEM	ii. Hydraulic oil and filtration system should be equipped with in-line, return line,
SAME AND ADDRESS OF THE PARTY O		1		L		suction strainer, dust alarm indicators and fan cooler.
	26	16		T		i. It should have both its level of comfort and safety to spend hours at a time
No.	6 5	15		1		inside.
	70	20	- 8		CABIN	ii. It should be equipped with air condition and heating system.
ACCOUNT OF	NR	E is				iii It should be capable to reduce sound and absorb impact while moving around
A SPERIOR OF THE PERIOR OF THE		,	_	+		
	X &	7 . 5				"Illo at a second party outficient for five years normal operation
	五	0 5	9	) [	FILTERS AND SPARE	should be provided with rates including 12 sets for each of cutting plates and
	CHANI	9				ripper points.
1	2	15 of willen			TOOL KIT	Tools required during operation, maintenance and repair of buildozer should
	H	Se.		10	TOOL KIT	be provided.
	A V	جع		Sr.		DESCRIPTION
1				N- 1	A STATE OF THE STA	
1		Note		1	Bids will be evaluated	keeping in view the cost of bulldozer. Filters and spares should be quoted seperately
1	1	11000		1 1	Sales de la company suill bor e	performed at manufacturer premises.
1				2		
		2 P		3		ozer the supplier will be responsible for successful commissioning.
				4		model bulldozer according to the specifications should be quoted.
,				5	Technical literature of	the quoted should be provided along with quotation.
						be covered under a warranty period of one year or 5000 operational hours (whicheve
				6	is earlier) after succe	ssful commissioning.
		10 m		K		manuals for each of operation, spare parts and maintenance of bulldozer should be
		1	-	7	provided.	
	100	4.0	Day.	CONTRACTOR AND ADDRESS OF		