

## VALVES

### HIGH PERFORMANCE BUTTERFLY VALVE

Limit Of Use	Rating	150 lbs
	Temperature °C	180 °C Max.
	Gauge Pressure	10 bars
Tests	Body Test	15 bars
	Seat Test	7 bars air under water

Service Fluids	Corrosive air & vapors
Type	Wafer Type
Body , Shaft & Pin	SS 304L
Seat	Viton/PTFE
DISC & Guide Stem	SS 304 L
Control	Hand Lever
Bushing	Glass-Backed PTFE
Room Conditions	Corrosive Atmosphere

#### Bill of Quantity:

Sr. No.	Size	Quantities
1	DN 100	25
2	DN 200	15

### HIGH PERFORMANCE BUTTERFLY VALVE

Limit Of Use	Rating	150 lbs
	Temperature °C	180 °C Max.
	Gauge Pressure	10 bars
Tests	Body Test	15 bars
	Seat Test	7 bars air under water

Service Fluids	Corrosive air & vapors
Type	Wafer Type
Body , Shaft & Pin	SS 304L
Seat	Viton/PTFE
DISC & Guide Stem	SS 304 L
Control	Gear Box/Worm Gear
Bushing	Glass-Backed PTFE
Room Conditions	Corrosive Atmosphere

#### Bill of Quantity:

Sr. No.	Size	Quantities
1	DN 200	10

## VALVES

---

### CHECK VALVES (NRV)

Limit Of Use	Rating	150 lbs
	Temperature °C	180 °C Max.
	Gauge Pressure	10 bars
Tests	Body Test	15 bars
	Seat Test	7 bars air under water

Service Fluids	Corrosive air & vapors
Type	Swing Check Valve
Body , Shaft & Pin	SS 304L
Sealing Structure	Soft Seal
Seat	Viton/PTFE
Nut	SS 304
Connection	Flanged
DISC & Stem	SS 304 L
Room Conditions	Corrosive Atmosphere

#### Bill of Quantity:

Sr. No.	Size	Quantities
1	DN 100	10
2	DN 200	10

#### Note:

1. The Supplier must be asked to provide the brochures/Catalog of original manufacturer along with quotation.
2. The Purchaser has the right to reject the incomplete offers without technical details/brochures.
3. The Valves of European/USA brands-origins (brands manufactured In China are also acceptable)