

## Car Valves, Aluminium, Black

- Lower weight as the valve is made of aluminium
- Black anodized which avoids spalling of the colour
- Aluminium valve cap with sealing
- Metal valves for tubeless tyres of cars and transporters
- Rounded valve base prevents tyre damages when mounting
- Plastic captive disc protects the wheel rim
- Compression stress up to 14 bar



Article No.	Article Description	QTY
3571 8	VALVE ALU BLACK ANODIZED 42MM	20

### Technical Data

Art. No.	For hole mm	Length mm	SW mm
3571 8	11.3	42	11

## Transporter Valves

- Metallic valves for tubeless tyres for vehicles and transporters
- Specially designed for transporter rims
- Rounded valve foot prevents tyre damage during assembly
- Valve foot with tool slit for trouble-free assembly and disassembly
- New sealing concept for increased safety and longer lifetime
- High temperature sealing
- With captive plastic disc for protecting the rim
- Valve cap must not be removed for assembly
- Up to max. 10 bar at +20°C




Article No.	Article Description	QTY
3571 3	METAL VALVE SW 12 41MM	20
3571 4	METAL VALVE SW 12 45MM	20

### Technical Data

Art. No.	For hole mm	Length mm	SW mm
35713	11.3	41	12
35714	11.3	45	12

## CVV Transporter Valves

- **For tubeless tyres, specially for transporters and truck campers**
- The patented CVV valve construction combines the strength of a metal valves together with the easy-to-use Snap-In rubber valve
- An optimized contour and the highly flexible sealing lip provide an optimum sealing for the rim
- The patented pressure disk keeps the valve safe and protects against high pressure
- For disassembly cut the pressure disk at the breaking point using pliers or a screwdriver and pull out the valve
- Pressure resistance up to 7 bar
- Temperature range from -40°C to +130°C



Patented pressure disk with breaking point for easy disassembly

Article No.	Article Description	QTY
3571 5	CVV TRANSPORTER VALVE 40MM	w 100
3571 6	CVV TRANSPORTER VALVE 47MM	w 100
3571 7	CVV TRANSPORTER VALVE 60MM	w 100

### Technical Data

Art. No.	For hole mm	Length mm
3571 5	11.3	40
3571 6	11.3	47
3571 7	11.3	60