

## DRILLING ACCESSORIES

Sr	Description/Specifications	Qty (Nos)
1.	Flush Joint drill pipe 6 meter long with: Outer Dia: 2-7/8 inches Wall Thickness: 9.19mm Joint Type (Pin & Box): 2-3/8" MAYHEW JUNIOR No. of flats for breakout wrench: 02 Nos. on both ends	50
2.	Spiral type integral blade tungsten carbide inserts stabilizer for hole size 3-7/8" with: Blade Length: 18 inches, Quantity of Blades: 03 Nos., Mid body Length: 1.50 meters, Mid Body Wall thickness: 9.19mm, Mid body Outer Dia: 2-7/8 inches Joint Type (Pin & Box): 2-3/8" MAYHEW JUNIOR, No. of flats for breakout wrench: 02 Nos. on both ends	12
3.	Drill Collar 3 meter long with: Outer Dia: 3-1/2 inches, Bore Size: 1-1/2 inches, Joint Type (Pin & Box): 2-3/8" MAYHEW JUNIOR, No. of flats for breakout wrench: 02 Nos. on both ends	06
4.	Heavy Duty swivel hoist plug with 2-3/8" MAYHEW JUNIOR pin	06
5.	Adopter sub 2-3/8" API IF pin to 2-3/8" MAYHEW JUNIOR box with mid body length 50cm having 2 Nos. flats for breakout wrench on both ends	06
6.	Adopter sub 2-3/8" MAYHEW JUNIOR pin to 2-3/8" API IF box with mid body length 50cm having 2 Nos. flats for breakout wrench on both ends	06
7.	Bit Sub 2-3/8" MAYHEW JUNIOR box to 2-3/8" API regular box	06
8.	Bit Sub 2-3/8" MAYHEW JUNIOR box to 2-7/8" API regular box	06

### **Important Note:**

1. Technical specifications of all accessories must be supported by literature/drawing etc.
2. No quotation without technical literature and drawings will be accepted.
3. Make and country of origin should be clearly mentioned in quotation.