

1 Electric Actuator

01 (No.)

- Type : FQ18
- Item Number : TMP0188964
- General Inspections:
- FQ18 A Explosion Proof INTEGRAL +3 50Hz 400V 93s
- Actuator's Speed (Rpm) : 0,16%
- Protection : IP67 EEx d IIC T5
- Box and Protection : Separate FPX (IP67 -20°C to 50°C)
- Class : A
- Output speed (RPM) : 0,16
- Operating time (s) : 93
- Max. torque (Nm) : 180
- Torque set O (Nm) : 180
- Torque set C (Nm) : 180
- Temperature : Standard -20°C to 60°C
- Output Flange : F10
- Output form : N/A
- Machining typ : Plain socket
- Manual command : Decutchable Ø160 mm
- Paint : BCPS-C3-01
- Painting process : Intermediate Corrosi
- Color : RAL 5002 MARINE BLUE
- Spring return time (Sec) : 3
- Motor : Electric 3Ph 400V 50Hz
- Power (kw) : 0,060
- End of travel limit switches : Opening :1 & Closing :1 - Type : SPDT
- Torque limit switches qty : Opening :0 & Closing :0 - Type : SPDT
- Coustomer's connection : Plug EEXD IIC 1x1" + 2x3/4" NPT
- Heater : 400 V 25 W
- Make : Bernard or equivalent

2 Electric Actuator

01 (No.)

- Type : FQ08
- Item Number : TMP0188977
- General Inspections:
- FQ08 A Explosion Proof INTEGRAL +3 50Hz 400V 33s
- Actuator's Speed (Rpm) : 0,45
- Protection : IP67 EEx d IIC T5
- Box and Protection : Separate FPX (IP67 -20°C to 50°C)
- Class : A
- Output speed (RPM) : 0,45
- Operating time (s) : 33
- Max. torque (Nm) : 80
- Torque set O (Nm) : 80
- Torque set C (Nm) : 80
- Temperature : Standard -20°C to 60°C
- Output Flange : F07
- Output form : N/A
- Machining typ : Plain socket
- Manual command : Standard Handwheel
- Paint : BCPS-C3-01
- Painting process : Intermediate Corrosi
- Color : RAL 5002 MARINE BLUE
- Spring return time (Sec) : 2
- Motor : Electric 3Ph 400V 50Hz
- Power (kw) : 0,060
- Control type : INTEGRAL+
- End of travel limit switches : Opening :1 & Closing :1 - Type : SPDT
- Torque limit switches qty : Opening :0 & Closing :0 - Type : SPDT
- Coustomer's connection : Plug EEXD IIC 1x1" + 2x3/4" NPT
- Heater : 400 V 25 W
- Make : Bernard or equivalent