

Specifications of Pyres tubes, fittings and tools.

S.No.	Item	Catalogue and make
1.	Sockets and Cones 1. 24/29 Socket: H128/13/0111 Cone: H127/12/0111 2. 29/32 Socket: H128/14/0111 Cone: H127/13/0111 3. 34/35 Socket: H128/15/0111 Cone: H127/14/0111 4. 40/38 Socket: H128/16/0111 Cone: H127/15/0111 5. 50/45 Socket: H128/18/0111 Cone: H127/18/0111	Brand : Jencons or equiv. Make: UK, USA, Europe, Japan
2.	Spherical joints 1. MS 13c Bore size 2mm 2. MS 13 Bore size 5mm 3. MS 19 Bore size 9mm 4. MS 29 Bore size 15mm 5. FS 13c Bore size 2mm 6. FS 13 Bore size 5mm 7. FS 19 Bore size 9mm 8. FS 29 Bore size 15 mm	Brand : Jencons or equiv. Make: UK, USA, Europe, Japan
3.	Adapters Quick fit DA 12, Socket: 14/23, Cone: 19/26 QAC-030-J DA 13, Socket: 14/23, Cone: 24/29 QAC-030-C DA 14, Socket: 14/23, Cone: 29/32 QAC-030-S DA 23, Socket: 19/26, Cone: 24/29 QAC-030-L DA 24, Socket: 19/26, Cone: 29/32 QAC-030-E DA 25, Spcket: 19/26, Cone: 34/35 QAC-030-U DA 26, Socket: 19/26, Cone: 40/38 QAC-030-N DA 27, Socket: 19/26, Cone: 45/40 QAC-030-W DA 29, Socket: 19/26, Cone: 55/44 QAC-030-P DA 34, Socket: 24/29, Cone: 29/32 QAC-030-Y DA 35, Socket: 24/29, Cone: 35/45 QAC-030-B DA 45, Socket: 29/32, Cone: 35/45 QAC-030-M DA 56, Socket: 34/35, Cone: 40/38 QAC-030-X Make: USA, UK, Europe	Brand : Gallenkamp or Equiv. Make: UK, USA, Europe, Japan
4.	Vacuum type straight adapters Quick fit 1. RA 13/33 socket: 24/29, Cone: 24/29 QAH-680-X 2. RA 3/22 socket: 19/29, Cone: 19/26 QAH-660-F 3. RA 3/23 socket: 19/26, Cone: 24/29 QAH-670-V 4. RA 3/34 socket: 29/32, Cone: 29/32 N/A 5. RA 3/35 socket: 29/32, Cone: 24/29 N/A	Brand: Gallenkamp or Equiv. Make: UK, USA, Europe, Japan
5.	Quickfit-Cone with screw cap adapters 1. ST 51/13, Thread: 13, cone: 14/23, dia screw cap: 6-7 mm QAJ-700-T 2. ST 52/13, Thread: 13, cone: 19/26, dia screw cap: 6-7 mm QAJ-710-M 3. ST 53/13, Thread: 13, cone: 24/29, dia screw cap: 6-7 mm QAJ-720-F 4. ST 54/13, Thread: 13, cone: 29/32, dia screw cap: 6-7 mm QAJ-770-V 5. ST 51/18, Thread: 18, cone: 14/23, dia screw cap: 7-8.5 mm QAJ-760-A 6. ST 52/13, Thread: 18, cone: 19/26, dia screw cap: 6-7 mm QAJ-770-Q 7. ST 53/13, Thread: 18, cone: 24/29, dia screw cap: 6-7 mm QAJ-780-J 8. ST 54/13, Thread: 18, cone: 29/32, dia screw cap: 6-7 mm QAJ-790-C 9. ST 53/24, Thread: 24, cone: 24/29, dia screw cap: 10.5-11.5 mm QAJ-830-V 10. ST 55/24, Thread: 24, cone: 34/35, dia screw cap: 10.5-11.5 mm QAJ-840-G Make: UK, USA, Europe, Japan	Brand: Gallenkamp or Equiv. Make: UK, USA, Europe, Japan
6.	Fractioning Columns 1. FC 1/12 Type: Dufton, Socket: 19/26 Cone: 19/26, length: 200mm QHD-030-X 2. FC 2/23 Type: Dufton, Socket: 24/29 Cone: 24/29, length: 360mm QHD-060-X 3. FC 1/13 Type: Vigreux, Socket: 24/29 Cone: 24/29, length: 200mm QHD-150-X 4. FC 3/23 Type: Vigreux, Socket: 24/29 Cone: 24/29, length: 200mm QHD-160-X	Brand : Gallenkamp Make: UK, USA, Europe, Japan

7.	Asbestos paper Tape 1. Width: 12-15 mm thickness: 0.25mm, Roll length: 230 M approx. H-146/1/0135 2. Width: 25 mm thickness: 0.25mm, Roll length: 230 M approx. H-146/1/0135 Make: UK, USA, Europe, Japan	Brand: Jencons or equiv. Make: UK, USA, Europe, Japan	Code: 7740 Make: UK, USA, Europe, Japan	8.	Pyrex Tubes Code: 7740 A. Outer Dia 65 mm, Wall Thickness: 2.4mm, Length: 1500 mm B. Outer Dia 75 mm, Wall thickness: 2.4 mm, length: 1500 mm C. Outer Dia: 80 mm, Wall thickness: 2.4 mm, length: 1500 mm	9.	Filter Disc Tubes a. Porosity: 0 Outer Dia: 12mm Outer Dia: 18mm Outer Dia: 22mm b. Porosity: 1 Outer Dia: 22mm Outer Dia: 18mm Outer Dia: 12mm Outer Dia: 22mm	10.	Ball Joints a. Male-female S-19	11.	Pyrex glass vials bottle with screw cap 1. 10 ml 11. 20 ml	12.	Glass cutter tool Gold tip ball end 134° carbide wheel with self-lubricating oil feed tipped. Anti-slip handle. Pistol grip, clear, replaceable wide head, 140°, corded. Steel wheel-cutter, Straight end, 120°.	13.	Manual glass tube cutter X" to 1X1/2" O.D tubes.	14.	Circle and oval glass cutter Equipped with 3 wheel turret. 50 mm to 1000 mm. Max. glass thickness: 15 mm. Diameter scale markings in English and metric. Includes straight edge attachment for straight line glass scoring.	15.	Micro-flame torch kit Fusion weld materials from <0.02mm to 3.0 mm glass and ceramic materials. With twin precision control valves and other accessories. Oxy-acetylene fuel. Spare and accessories: For smooth running of years.	16.	Glass collar/step making mold/tool different sizes	Make: Fletchers or equivalent, USA, UK, Japan
----	--	--	--	----	---	----	--	-----	------------------------------------	-----	--	-----	---	-----	---	-----	---	-----	--	-----	--	---