

Sr#	Description	Qty
1	<b><u>GLOBE VALVE:</u></b> Function: Throttling/regulation Nominal Pressure:PN16 Wheel Type: Rising Stem End Connection: Flanged Connection/Flanged to DIN- 2633 or equivalent Flange Type: Raised face Material of Construction: Stainless Steel Pressure/temperature rating material specification: To be specified by the manufacturer Size: 8"Ø	04
2	<b><u>GATE VALVE:</u></b> Function: Isolation Nominal Pressure: PN16 Wheel Type: Rising Stem End Connection: Flanged connection/ flanged to DIN-2633 or equivalent. Flange Type: Raised face Material of Construction: Stainless Steel Hydrostatic test pressure, pressure/temperature rating material specification: To be specified by the manufacturer Size: 10" Ø	06
3	<b><u>GATE VALVE:</u></b> Function: Isolation Nominal Pressure: PN16 Wheel Type: Rising Stem End Connection: Flanged connection/flanged to DIN-2633 or equivalent Flange Type: Raised face Material of Construction: Stainless Steel Hydrostatic test pressure, pressure/temperature rating material specification: To be specified by the manufacturer Size: 8" Ø	12
4	<b><u>GATE VALVE:</u></b> Function: Isolation Nominal Pressure: PN16 Wheel Type: Rising Stem End Connection: Flanged connection/flanged to DIN-2633 or equivalent. Flange type: Raised face Material of Construction: Stainless Steel. Hydrostatic test pressure, pressure/temperature rating material specification: To be specified by the manufacturer Size:48" Ø	04

**Notes:**

- a. Make: Kitz, Hattersley, Flowcon, TYCO, Duker Germany, Tran Valves, CEPEX, KSB Germany.
- b. Origin: EU/USA/Japan